







CHASSIS®

Classification ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile

Size* 7" x 48" / 177.8 mm x 1219.2 mm (nom)

Overall Thickness* 0.08" / 2.0 mm

Wear Layer 6 mil / 0.15 mm, featuring **auff Shield** finish

Edge Square

Standard Colors 8 standard planks

Installation Method Glue Down

Wear Limited Warranty 20 Year Residential / 10-Year Light Commercial

Recycled Content This product contains recycled content.

ASTM F 925

ASTM E 648-06

ASTM E 492-09

ASTM E 989-06

ASTM F 137

ASTM F 1514

ASTM F 2199

100% recyclable post-use

Packaging PLANK

Product Testing
Chemical Resistance

Critical Radiant Flux

Dimensional Stability

+STC Sound Testing

+IIC Sound Testing

Resistance to Heat

Flexibility

32.72 ft² (3.04 m²) per carton 14 pieces per carton 85 cartons per pallet 18 pallets per 20' container

Passed

Passed

Passed

Passed

+STC 61 +IIC 64

Class I, CRF ≥0.45

Weight Per Carton 25.57 lbs / 11.60 kg


















BETTER I WEAR LIMITED WARRANTY







Spitfire CHA 7477 - Heavy Shade Variation



Backbone CHA 7478 - Heavy Shade Variation



Caspas CHA 7479



Armature CHA 7480 - Heavy Shade Variation



Motorcoach CHA 7481



suspension CHA 7402



Farnham CHA 7483



Shepherd CHA 7484

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images. Visit www.earthwerks.com for full product and warranty details.

^{*}All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.