



CHASSIS® PRO

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 177.8 mm x 1219.2 mm (nom)
Overall Thickness*	0.12" / 3.0 mm
Wear Layer	20 mil / 0.50 mm, featuring Stiff Shield finish
Edge	Square
Standard Colors	8 standard planks
Installation Method	Glue Down
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial
Recycled Content	This product contains recycled content. 100% recyclable post-use
Packaging	PLANK 27.98 ft ² (2.60 m ²) per carton 12 pieces per carton 65 cartons per pallet 17 pallets per 20' container
Weight Per Carton	32.88 lbs / 14.91 kg



Armature CPR-9260 (Heavy Shade Variation)

Product Testing


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 67
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



PREMIUM I WEAR LIMITED WARRANTY



SCS Certified



Spitfire CPR 9257 - Heavy Shade Variation



Backbone CPR 9258 - Heavy Shade Variation




Caspas CPR 9259




Armature CPR 9260 - Heavy Shade Variation



Motorcoach CPR 9261



Suspension CPR 9262



Farnham CPR 9263



Shepherd CPR 9264

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images. Visit www.earthwerks.com for full product and warranty details.