



**Glazed Porcelain Tile**

# Fusion

|                                |  |
|--------------------------------|--|
| <b>Product Size*</b>           | 12" x 24"  |
| <b>Thickness*</b>              | 8 mm   |
| <b>Number of Faces</b>         | 25   |
| <b>DCOF</b>                    | ≥ 0.42   |
| <b>Breaking Strength</b>       | > 275 lbs  |
| <b>Freeze Resistant</b>        | Resistant  |
| <b>Stain Resistant</b>         | Class A  |
| <b>Recommended Grout Joint</b> | 3/16 Pressed   |
| <b>Packaging</b>               | 13.79 ft <sup>2</sup> per carton<br>7 pieces per carton<br>40 cartons per pallet |
| <b>Weight Per Carton</b>       | 51.66 lbs  |




Chalk - EAT900052E

\*All measurements are nominal.



Chalk - EAT900052E



Sand - EAT900053E



Silver - EAT900055E

**ATTENTION:** Be sure to specify the product with the proper wear rating for the specific area to be covered.

- > Before setting the tiles, verify the grade, shade & caliber numbers assuring that they are the same on all cartons.
- > Shade variation is inherent to ceramic tile. Tile should be combined from several cartons during installation to ensure proper blend.
- > Use only approved setting material recommended for ceramic tile on properly prepared floors & walls. Use expansion joints as required.

**VERY IMPORTANT**

Claims will not be accepted after installation

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.