



**Glazed Porcelain Tile**

# Selwyn

<b>Product Size*</b>	12" x 24" Floor Tile
<b>Thickness*</b>	7.6 mm
<b>Number of Faces</b>	10
<b>DCOF</b>	≥ 0.42
<b>Breaking Strength</b>	> 275 lbs
<b>Freeze Resistant</b>	Resistant
<b>Stain Resistant</b>	Class A
<b>Recommended Grout Joint</b>	3/16 Pressed
<b>Packaging</b>	15.6 ft <sup>2</sup> per carton 8 pieces per carton
<b>Weight Per Carton</b>	64.70 lbs



Bianco Calacatta - EATSL601224HD1P6

\*All measurements are nominal.

Residential	Commercial	Floor	Wall	Wet Area



Water Absorption  
≤ 0.5%



Shade Variation  
V4



Finish  
Matte



Bianco Calacatta - EATSL601224HD1P6

**ATTENTION:** Be sure to specify the product with the proper wear rating for the specific area to be covered.

- > Before setting the tiles, verify the grade, shade & caliber numbers assuring that they are the same on all cartons.
- > Shade variation is inherent to ceramic tile. Tile should be combined from several cartons during installation to ensure proper blend.
- > Use only approved setting material recommended for ceramic tile on properly prepared floors & walls. Use expansion joints as required.

**VERY IMPORTANT**

Claims will not be accepted after installation

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.