



CHASSIS® ADVANTAGE SPC PLUS

CLASSIFICATION	ASTM F-3261-17 Resilient flooring in modular format with Solid Polymeric Core
SIZE	7" x 48" / 183 mm x 1220 mm (nom)
OVERALL THICKNESS	0.18" / 4.5 mm (nom) (3.5 mm + 1 mm cushion backing)
WEAR LAYER	12 mil / 0.30 mm featuring <i>Tuff Shield</i> ® finish
CONSTRUCTION	ABA SPC
EDGE	Bevel
STANDARD COLORS	8 standard colors
INSTALLATION METHOD	Angle/Angle
WEAR LIMITED WARRANTY	30-Year Residential / 20-Year Light Commercial
RECYCLED CONTENT	This product contains no recycled content. 100% recyclable post-use.
PACKAGING	28.84 ft ² (2.68 m ²) per carton 12 pieces per carton 55 cartons per pallet
WEIGHT PER CARTON	42.88 lbs / 19.45 kg



Caspas - CAS-3801CB

PRODUCT TESTING

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-17	Class I, CRF >1.13
Dimensional Stability	ASTM 2199	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Slip Resistance	ASTM C 1028	Passed



BEST | Wear Limited Warranty




Caspas CAS-3801 CB




Armature CAS-3802 CB (Heavy Shade Variation)



Motorcoach CAS-3803 CB




Suspension CAS-3804 CB



Farnham CAS-3805 CB



Shepherd CAS-3806 CB



Spitfire CAS-3807 CB (Heavy Shade Variation)



Backbone CAS-3808 CB (Heavy Shade Variation)

*All measurements are nominal

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit www.STCfloors.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.