



CHASSIS® PRO SPC PLUS

CLASSIFICATION	ASTM F-3261-17 Resilient flooring in modular format with Solid Polymeric Core
SIZE	7" x 48" / 183 mm x 1220 mm (nom)
OVERALL THICKNESS	0.20" / 5.0 mm (nom) (4 mm + 1 mm cushion backing)
WEAR LAYER	20 mil / 0.50 mm featuring Cliff Shield MAX finish with anti-bacterial protection
CONSTRUCTION	ABA SPC
STANDARD COLORS	8 standard colors
INSTALLATION METHOD	Angle/Angle
WEAR LIMITED WARRANTY	Lifetime Residential Wear Limited Warranty / 30-Year Commercial Wear Limited Warranty
RECYCLED CONTENT	This product contains no recycled content. 100% recyclable post-use.
PACKAGING	7" x 48" 28.84 ft ² (2.68 m ²) per carton 12 pieces per carton 45 cartons per pallet
WEIGHT PER CARTON	49.45 lbs / 22.43 kg



Backbone - CHS-5488CB

PRODUCT TESTING

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-17	Class I, CRF ≥0.45
Dimensional Stability	ISO 23999	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-15A	Passed
Static Load Limit	ASTM F 970	Passed
Slip Resistance	ASTM C 1028	Passed
*IIC Sound Testing	ASTM E 989-06	*IIC 61




PREMIUM I Wear Limited Warranty



SCScertified



Caspas CHS-5479 CB



Farnham CHS-5483 CB




Armature CHS-5480 CB (Heavy Shade Variation)




Shepherd CHS-5484 CB



Motorcoach CHS-5481 CB



Spitfire CHS-5487 CB (Heavy Shade Variation)



Suspension CHS-5482 CB



Backbone CHS-5488 CB (Heavy Shade Variation)

*Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.