



FOOTPRINTS PLUS XL

Classification	ASTM F 3261-17 Resilient flooring in modular format with Solid Polymeric Core
Size*	9" x 60" / 225 mm x 1522 mm
Overall Thickness*	0.24" / 6 mm (5 mm + 1 mm cushion backing)
Wearlayer	20 mil / 0.50 mm, featuring Tuff Shield finish
Edge	Painted Bevel
Standard Colors	4 standard colors
Installation Method	Fold Down
Wear Limited Warranty	Lifetime Residential / 30-Year Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use
Packaging	18.43 ft ² (1.71 m ²) per carton 5 pieces per carton 56 cartons per pallet 18 pallets per 20' container
Weight Per Carton	38.18 lbs / 17.32 kg



Rowhouse - LNA 394CB

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-17	Class I, CRF ≥ 0.45
Dimensional Stability	ISO 23999	Passed
*STC Sound Testing	ASTM E 413-16	*STC 62
*IIC Sound Testing	ASTM E 989-06	*IIC 70
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-15A	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed



LNA 391CB - Outerbanks
(Heavy Shade Variation)



LNA 393CB - Sundew



LNA 392CB - Pier
(Heavy Shade Variation)



LNA 394CB - Rowhouse
(Heavy Shade Variation)

*Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.