



# PARKHILL® EIR PLUS

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 180 mm x 1220 mm (nom)
Overall Thickness*	0.28" / 7 mm (6 mm + 1 mm cushion backing)
Wearlayer	20 mil / 0.50 mm, featuring <b>Tuff Shield</b> finish
Edge	Micro Bevel
Standard Colors	6 EIR planks
Installation Method	Angle/Angle
Wear Limited Warranty	Lifetime Residential / 30-Years Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use
Packaging	23.64 ft <sup>2</sup> (2.20 m <sup>2</sup> ) per carton 10 pieces per carton 60 cartons per pallet 16 pallets per 20' container
Weight Per Carton	37.51 lbs / 17 kg



Brown Bear - PKH 383 CB

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.91
Dimensional Stability	ASTM F 2199	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
*STC Sound Testing	ASTM E 492-09	*STC 60
*IIC Sound Testing	ASTM E 989-06	*IIC 70




Copperbrooke PKH 347 CB (Moderate Shade Variation)



Otter PKH 382 CB (Moderate Shade Variation)



Grove Park PKH 351 CB (Moderate Shade Variation)



Brown Bear PKH 383 CB (Moderate Shade Variation)



White Fang PKH 381 CB (Moderate Shade Variation)



Wild Hare PKH 384 CB (Heavy Shade Variation)

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images. Visit [www.earthwerks.com](http://www.earthwerks.com) for full product, warranty details and installation guidelines. All specifications and offerings subject to change without notice.

\*Sound Testing will vary depending on the specific floor/ ceiling assembly.