



# PAVILION™ Plank

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	6" x 36" / 152.4 mm x 914.4 mm (nom)
Overall Thickness*	0.08" / 2.0 mm
Wearlayer	8 mil / 0.20 mm, featuring <b>Tuff Shield</b> finish
Edge	Square
Standard Colors	8 standard planks
Installation Method	Glue Down
Wear Limited Warranty	20-Year Residential Wear Limited Warranty / 10-Year Light Commercial Wear Limited Warranty
Recycled Content	This product contains no recycled content. 100% recyclable post-use
Packaging	35.95 ft <sup>2</sup> (3.34 m <sup>2</sup> ) per carton 24 pieces per carton 72 cartons per pallet 20 pallets per 20' container
Weight Per Carton	26.50 lbs / 12.02 kg



Midtown SCP 1684

## Product Testing


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
+STC Sound Testing	ASTM E 492-09	+STC 61
+IIC Sound Testing	ASTM E 989-06	+IIC 64




BETTER I WEAR LIMITED WARRANTY



SCS certified



Tenement SCP 1681




Park Place SCP 1685



Tower Block SCP 1682




Regency SCP 1686




Maisonette SCP 1683



Elevation SCP 1687



Midtown SCP 1684



Townhouse SCP 1688

\*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.  
Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.