



# PAVILION<sup>®</sup> Plank

Classification	ASTM F 1700 Class III, type A or B Solid Vinyl Floor Tile
Size*	6" x 36" / 152.4 mm x 914.4 mm
Overall Thickness*	0.08" / 2.0 mm (nom)
Wear Layer	8 mil / 0.20 mm featuring <b>Tuff Shield</b> finish
Edge	Square
Standard Colors	8 colors
Installation Method	Glue-Down
Wear Limited Warranty	20-Year Residential / 10-Year Light Commercial
Recycled Content	This product contains no recycled content.
Packaging	35.95 ft <sup>2</sup> (3.34 m <sup>2</sup> ) per carton 24 pieces per carton 72 cartons per pallet
Weight Per Carton	26.50 lbs / 12.02 kg



Midtown SCP 1684

## Product Testing


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
STC Sound Testing	ASTM E 492-09	STC 61
IIC Sound Testing	ASTM E 989-06	IIC 64



BETTER I WEAR LIMITED WARRANTY




Tenement SCP 1681



Park Place SCP 1685



Tower Block SCP 1682



Regency SCP 1686




Maisonette SCP 1683



Elevation SCP 1687



Midtown SCP 1684



Townhouse SCP 1688

\*All measurements are nominal. Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images.

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details & installation guidelines. All specifications & offerings are subject to change without notice.