



Regatta® Plus XL

Classification	ASTM F 3261-17 Resilient flooring in modular format with Solid Polymeric Core
Size*	9.5" x 60" (nom)
Overall Thickness*	5.0 mm (4 mm + 1 mm cushion backing)
Wear Layer	20 mil featuring Tuff Shield MAX with anti bacterial finish
Construction	Co-Extruded ABA SPC
Edge	Painted Bevel
Standard Colors	4 colors
Installation Method	Angle / Angle
Wear Limited Warranty	Lifetime Residential / 30-Year Light Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use.
Packaging	31.50 ft² (2.93 m²) per carton 8 pieces per carton 52 cartons per pallet
Weight Per Carton	52.91 lbs / 24.00 kg



Beacon - CVA-359CB

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I
Dimensional Stability	ISO 23999	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-15A	Passed
Static Load Limit	ASTM F 970	Passed
Slip Resistance	ASTM C 1028	Passed
IIC Sound Testing	ASTM E 989	IIC 61
Delta IIC Sound Testing	ASTM E 2179	Delta IIC 29
STC Sound Testing	ASTM E 90 / E 413	STC 56



Captain CVA-357CB



Anchor CVA-360CB



Beacon CVA-359CB



Sail CVA-361CB

All specifications and offerings subject to change without notice. Sound Testing will vary depending on the specific floor/ ceiling assembly.

*All measurements are nominal.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images. Please visit www.STCfloors.com for full warranty details and installation guidelines.