



# Reveille® Plus XL

Classification	ASTM F 3261-17 Resilient flooring in modular format with Solid Polymeric Core
Size*	9" x 60" (nom)
Overall Thickness*	5.0 mm (4 mm + 1 mm cushion backing)
Wear Layer	20 mil featuring <b>Tuff Shield MAX</b> with anti bacterial finish
Construction	Co-Extruded ABA SPC
Edge	Bevel
Standard Colors	6 colors
Installation Method	Angle / Angle
Wear Limited Warranty	Lifetime Residential / 30-Year Light Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use.
Packaging	30.18 ft <sup>2</sup> (2.80 m <sup>2</sup> ) per carton 8 pieces per carton 56 cartons per pallet
Weight Per Carton	50.99 lbs / 23.13 kg



Suitable - BRV-352CB


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I
Dimensional Stability	ASTM F 23999	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-15A	Passed
Static Load Limit	ASTM F 970	Passed
Slip Resistance	ASTM C 1028	Passed
IIC Sound Testing	ASTM E 989	IIC 61
Delta IIC Sound Testing	ASTM E 2179	Delta IIC 29
STC Sound Testing	ASTM E 90 / E 413	STC 56



Debonair BRV-350CB




Sanderling BRV-353CB




Repose BRV-351CB



Ethereal BRV-354CB



Suitable BRV-352CB



Umber BRV-355CB

All specifications and offerings subject to change without notice. Sound Testing will vary depending on the specific floor/ ceiling assembly.

\*All measurements are nominal.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images. Please visit [www.STCfloors.com](http://www.STCfloors.com) for full warranty details and installation guidelines.