



# SHERBROOKE® PLUS

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 180 mm x 1220 mm (nom)
Overall Thickness*	0.26" / 6.5 mm (5.5 mm + 1mm cushion backing)
Wearlayer	12 mil / 0.30 mm, featuring <b>Diff Shield</b> finish
Edge	Micro Bevel
Standard Colors	6 standard planks
Installation Method	Angle/Angle
Wear Limited Warranty	30-Years Residential / 20-Years Light Commercial
Recycled Content	This product contains no recycled content. 100% recyclable post-use
Packaging	23.64 ft <sup>2</sup> (2.20 m <sup>2</sup> ) per carton 10 pieces per carton 65 cartons per pallet 16 pallets per 20' container
Weight Per Carton	34.86 lbs / 15.80 kg



Saddle - SHB 2168 CB

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.91
Dimensional Stability	ASTM F 2199	Passed
*STC Sound Testing	ASTM E 492-09	*STC 61
*IIC Sound Testing	ASTM E 989-06	*IIC 71
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-06	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed




Jackson Pine SHB 2167 CB



Saddle SHB 2168 CB



Burlap SHB 2169 CB



Linen SHB 2170 CB



Natural SHB 2171 CB



Chestnut SHB 2172 CB

\*Sound Testing will vary depending on the specific floor/ ceiling assembly.

Please visit [www.earthwerks.com](http://www.earthwerks.com) for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.