



TAVERN™ PLUS

Classification	ASTM F-3261-17 Resilient flooring in modular format with Solid Polymeric Core
Size*	7" x 48" / 180 mm x 1220 mm
Overall Thickness*	0.20" / 5.0 mm (4 mm + 1 mm cushion backing)
Wear Layer	12 mil / 0.30 mm featuring Tuff Shield finish
Edge	Micro Bevel
Standard Colors	6 standard colors
Installation Method	Fold-Down
Wear Limited Warranty	30-Year Residential / 20-Year Light Commercial
Recycled Content	This product contains no recycled content. 100 % recyclable post use.
Packaging	18.91 ft ² (1.76 m ²) per carton 8 pieces per carton 65 cartons per pallet 18 pallets per 20' container
Weight Per Carton	32.25 lbs / 14.63 kg



Dubbel - TVN 506 CB


Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648-17	Class I, CRF ≥ 0.92
Dimensional Stability	ISO 23999	Passed
Residual Indentation	ASTM F 1914	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662-15A	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 387	Passed
STC Sound Testing	ASTM E 413-16	STC 62
IIC Sound Testing	ASTM E 989-06	IIC 71




BEST WEAR LIMITED WARRANTY




SCScertified



Pale Ale TVN 501 CB



Dunkel TVN 504 CB



Pilsner TVN 502 CB



Imperial TVN 505 CB (Heavy Shade Variation)



Pint TVN 503 CB



Dubbel TVN 506 CB

* Products within this collection may feature a high degree of shade variation from plank to plank.

*All measurements are nominal. + Sound Testing will vary depending on the specific floor/ceiling assembly. Please visit www.earthwerks.com for full warranty details and installation guidelines. All specifications and offerings subject to change without notice.