



Reposado™

Classification	ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile
Size*	7" x 48" / 178 mm x 1220 mm
Overall Thickness*	0.08" / 2.0 mm (nom)
Wear Layer	8 mil / 0.20 mm featuring Tuff Shield finish
Edge	Square
Standard Colors	4 colors
Installation Method	Glue-Down
Wear Limited Warranty	20-Year Residential / 10-Year Light Commercial
Recycled Content	This product contains recycled content. 100% recyclable post-use.
Packaging	51.34 ft ² (4.77 m ²) per carton 22 pieces per carton 60 cartons per pallet
Weight Per Carton	37.70 lbs / 17.10 kg



Sunrise RPS-302

Product Testing

Chemical Resistance	ASTM F 925	Passed
Critical Radiant Flux	ASTM E 648	Class I, CRF ≥0.91
Dimensional Stability	ASTM F 2199	Passed
Flexibility	ASTM F 137	Passed
Resistance to Heat	ASTM F 1514	Passed
Resistance to Light	ASTM F 1515	Passed
Smoke Density	ASTM E 662	Passed
Static Load Limit	ASTM F 970	Passed
Thickness	ASTM F 386	Passed
+STC Sound Testing	ASTM E 90 / E 413	+STC 61
+IIC Sound Testing	ASTM E 492 / E 989	+IIC 64



BETTER WEAR LIMITED WARRANTY




SCS certified.



Paloma RPS-301



Sunrise RPS-302



Matador RPS-303



Siesta RPS-304

*All measurements are nominal. +Sound Testing will vary depending on the specific floor/ ceiling assembly.

Samples are intended to be a reference for product visuals and may not represent all color, shade, pattern, and texture variations. Actual product may differ from small swatches, printed media, or digital computer images. Visit www.earthwerks.com for full product and warranty details.