



**INTERTECHNIK**  
*hear you are®*



### AUDYN Q4 HIGH GRADE MKP FOIL CAPACITORS

Available values: 0.01uF - 100Uf, tolerance: +/-5%.

Voltage rating: 400 Vdc. Loss Angle Tan: 0.0003 at 1kHz/20°C.

Tightly wound core to prevent microphonic effects. Tinned copper wires.

Foil thickness: 8um: 0.10uF - 0.22uF; 6um: 0.33uF - 0.68uF; 6um: 0.82uF – 100uf.

### SIZE CHART

0.01uf 11x7mm	0.1uf 18x9mm	0.15uf 18x9mm	0.22uf 18x10mm
0.33uf 18x10mm	0.47uf 18x12mm	0.56uf 18x13mm	0.68uf 18x14mm
0.82uf 23x13mm	1.0uf 23x14mm	1.5uf 23x16mm	2.0uf 23x16mm
2.2uf 23x16mm	2.5uf 23x17mm	2.7uf 23x18mm	3.0uf 35x14mm
3.3uf 35x16mm	3.9uf 35x18mm	4.3uf 35x19mm	4.7uf 35x19mm
5.0uf 35x20mm	5.2uf 35x20mm	5.6uf 35x21mm	6.2uf 35x22uf
6.8uf 35x23uf	7.5uf 35x24mm	8.2uf 35x25mm	10uf 35x27mm
12uf 35x27mm	13uf 35x28mm	15uf 43x28mm	17uf 43x29
18uf 43x37mm	20uf 43x37mm	22uf 43x37mm	25uf 45x35mm
27uf 45x38mm	30uf 45x38mm	33uf 56x38mm	36uf 45x44mm
40uf 45x44mm	47uf 56x45mm	50uf 60x42mm	52uf 60x43mm
60uf 60x47mm	68uf 62x52mm	75uf 60x53mm	82uf 62x61mm
90uf 60x58mm	100uf 62x61mm		