



The bipolar electrolytic capacitors of the **ECap AC · Audio Coupling & Signal Cap PLAIN** series are made of smooth and thus low-loss foils. This has a positive effect on the sound characteristics. Music is reproduced in more details and nuances. Highlights:

Capacity range	1µF to 200µF
Electric strength	AC23 DC35 · AC35 DC50 · AC50 DC70
Temperature range	-40°C/-40°F to 85°C/+185°F
Service life [U <sub>R</sub> · I <sub>R</sub> ]	5,000 hours at +85°C/+185°F
Loss angle [tan α]	0.025 @ 1kHz

**ECAP70**

**Electrolytic capacitors 70 VDC / 50 VAC, plain**

Capacity [µF] ±5%	Body Ø * L [mm]	Wire Ø * L [mm]	[€]
1,0	10 * 20	0.8 * 40	0,79
1,5	10 * 20	0.8 * 40	0,89
2,2	10 * 30	0.8 * 40	0,99
2,7	10 * 30	0.8 * 40	1,09
3,3	10 * 30	0.8 * 40	1,19
3,9	10 * 30	0.8 * 40	1,29
4,7	10 * 30	0.8 * 40	1,39
5,6	12 * 30	0.8 * 40	1,49
6,8	12 * 30	0.8 * 40	1,59
8,2	14 * 37	0.8 * 40	1,79
10	14 * 37	0.8 * 40	1,99
15	18 * 39	0.8 * 40	2,49
22	25 * 38	0.8 * 40	2,99
33	25 * 38	0.8 * 40	3,99
47	25 * 49	0.8 * 40	4,99

**ECAP50**

**Electrolytic capacitors 50 VDC / 35 VAC, plain**

Capacity [µF] ±5%	Body Ø * L [mm]	Wire Ø * L [mm]	[€]
47	25 * 38	0.8 * 40	3,99
56	25 * 49	0.8 * 40	4,99
68	25 * 49	0.8 * 40	5,99
82	30 * 50	0.8 * 40	6,99
100	30 * 50	0.8 * 40	7,99