



**WACKER  
NEUSON**  
*all it takes!*

## HYDRO TECHNOLOGY SYSTEMS

### GP 3800A

Portable Generators  
SKU# 0620974



### Portable Power With Dependability & Versatility

This Wacker Neuson Portable Premium Generator GP 3800A is designed for construction jobs or anywhere high performance and dependability is required. It's heavy-duty frame and premium components produce problem-free operation in the most brutal environments. The Wacker Neuson GP 3800A is quiet and compact designed for power a large range of equipment with high starting amperage tools.

- Greatest in class tool starting and voltage regulation due to step-start generator technology with AVR (automatic voltage regulation) and excitation winding.
- Central GFCI (neutral bonded to ground) sensor system eliminates common GFI outlet failures and offers protection on all receptacles including 240 Voltage. Greatly achieves the latest NEC and OSHA jobsite standards.
- Exclusive auto-idle control with time delay system automatically reduces the engine to a low speed reducing fuel consumption, noise and wear.
- Complete wrap-around frame with dual cross-member support, high impact polyethylene fuel tank and heavy-duty shock-mounting combine to provide phenomenal impact protection.
- Dependable Honda engine with low oil shutdown. Completely compliant with the latest EPA emissions regulations.



## Technical specifications

### Portable Premium Generators

#### Dimensions

L x W x H Overall	27 x 21 x 21.2 in
L x W x H Shipping	28 x 21.5 x 23.2 in
Weight Dry	167.8 lb
Shipping weight without Fuel	173 lb

#### Operating data

Operating weight with Fuel	198 lb
Circuit breaker AC - 1 Phase 2 Pole	16 A
Receptacles AC Outlet	(2)125V,20A Duplex
Receptacles AC Outlet	125V,20A Duplex
Receptacles AC Outlet	125V,30A Twist Lock

#### Electrical system

Electrical power Max Output	3,800 W
Electrical power Continuous Power	3,400 W
Voltage AC - 1 Phase	120/ 240 V
Current AC - 1 Phase	28.3/ 14.2 A
Frequency	60 Hz
Power factor	1 cos $\Phi$ 1~
Generator model	AVR With Brushes
Power Rating Specification	SAE J1349

#### Engine / Motor

Engine / Motor	Honda
Engine / Motor manufacturer	GX240 RT2
Cylinder	1
Displacement	16.5 in <sup>3</sup>
Operating performance	7.1 kW
RPM / speed Operating	3,600 rpm
Tank capacity Fuel	4.94 US qt



Tank capacity Oil	1.2 US gal
Fuel type	Gasoline
Fuel consumption	0.63 US gal/h
Runtime	7.8 h

**Please note**

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.