

HYDRO TECHNOLOGY SYSTEMS



P 35A Vibratory Screeds



Reliable performance and operator comfort

When finishing concrete slabs, Wacker Neuson's wet screed can fit the demands of every job site with a variety of blade lengths, plus each unit is designed to fit the demands of every operator. It's unique twin handle system is fully height and angle adjustable offering maximum operator comfort. In addition, two isolators and specialized lower handle mount design reduce vibration to the operator. The squeeze grip handle is also foldable for easy transport and storage.

- Adjustable eccentric weights can be adjusted to seven different positions allowing the unit's force to be appropriately matched to the application.
- Lightweight unit features lifting handle for easy transport.
- High production unit for quick and accurate strike-off of concrete slabs with or without the support of grade stakes and forms.
- Fully enclosed exciter for operator production and low maintenance.

hydrotechnologysystems.us Page: 1 / 2





Technical specifications

Wet screed P 35A

Weight Operating	34.2 lb		
Engine / Motor	Air-cooled single-cylinder four-cycle gasoline engine		
Engine / Motor manufacturer	Honda GX35		
Displacement	2.2 in ³		
Engine performance	1.0 (1.3) kW (hp)		
at rpm	7,000 rpm		
Tank capacity	0.7 US qt		
Fuel consumption	0.2 US gal/h		
Length machine	36.7 in		
Width machine	36.7 in		

4 ft - 8 ft (1200-2400 mm) blade lengths

	SB 4F	SB 15M	SB 6F	SB 20M	SB 8F
Weight Ib	8.4	10.1	11.9	13.4	16.8
Length in	47.2	59.1	70.9	78.7	94.4
Width in	6.5	6.5	6.5	6.5	6.5

10 ft - 16 ft (3000 - 4900 mm) blade lengths

	SB 10F	SB 12F	SB 14F	SB 16F
Weight Ib	20.9	25.1	29.3	33.5
Length in	118.1	145.7	169.3	192.9
Width in	6.5	6.5	6.5	6.5

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

hydrotechnologysystems.us Page: 2 / 2