

ITEM	SPECIFICATION
------	---------------

**TECHNICAL SPECIFICATIONS**

Dimensions	Plank: Width: 5.1" (129.5mm) Length: 25.4" (645mm)   Chevron Plank: Width: 18" (452mm) Length: 53" (1232mm)
Thickness	Overall: 0.27" (7mm) Wear Layer: 0.55 mm (22mil)
Profile	Micro-Bevel Edges
Coverage	Planks: 14.5 sq.ft (1.35 sq.m) per box, 725 sq. ft (67 sq.m) per pallet   Chevron Planks: 26.5 sq.ft (2.46 sq. m) per box, 1,139.5 sq.ft (105.86 sq. m) per pallet
Planks per Box	Planks: 16 Planks   Chevron Planks: 4 Planks
Boxes per Pallet	Planks: 50 Boxes   Chevron Planks: 43 Boxes
Weight	Planks: 30.6 lbs. (13.9 kg) per box, 1,530 lbs. (695 kg) per pallet   Chevron Planks: 58 lbs. (26.3 kg) per box, 2,494 lbs. (1131 kg) per pallet
Composition	100% Virgin Premium SPC (Stone Polyvinyl Composite)
Type	Floating-floor with easy-install industry-leading UNilin™ Locking System
Application	Residential & Commercial
Surface Treatment	4x UV Coating, Anti-Microbial Embedded with Ceramic bead Finish
Visual Pattern Repeat	Approx. every 1,200mm (39.37in)
Print pattern repeat	Approx. 1 plank in every 10 cartons
Backing	Moisture Resistant
Warranty	10 Year Limited Commercial 25 Year Limited Residential

**PERFORMANCE**

Classification	EN ISO 10582 Domestic Heavy Class 23 Commercial Very Heavy Class 34 Light Industrial Heavy Class 43	Slip Resistance — Wet	Din 51130	Surpasses	
Size & Straightness	EN 426	Passes	Chemical Resistance	EN 423	No Effect
Thickness	EN 428	Passes	Reaction To Fire	EN 13501-1	Bfl-S1 Classification
Dimensional Stability	EN 434	Surpasses	100% Phthalate Free		Yes
Flexibility	EN 435	Passes	100% Waterproof		Yes
Residual Stability	EN 433	Surpasses	Antimicrobial		Yes
Castor Chair	ISO 4918	Passes	Environmental Certification		Floorscore Certified
Color Fastness To Light	ISO 105-B02	Surpasses	Scratch/Abrasion		Excellent
Product-Content Safety	Reach Svhc 163	Passes	Slip Resistance		Class Ds
Formaldehyde Emission	EN 717-1	0 Mg/M	lic (Impact Isolaton Class)	Impact Sound Absorption	72 Db
Slip Resistance — Dry	EN 13893	Surpasses	STC (Sound Transmission Class) Traveling Sound Absorption		71 Db
			Use With Radiant Flooring		Recommended



**LUCIDA**<sup>®</sup>  
SURFACES

setting life's stage™

**Lucida Surfaces USA**

55 Haul Road  
Wayne, NJ 07470  
+1 (845) 877-7008

**Lucida Surfaces Canada**

8620 Rue Pascal-Gagnon  
Montreal QC H1P 1Z1  
+ (514) 587-9926

LucidaSurfaces.com