TECHNICAL SPECIFICATIONS

Dimensions	Plank: Width: 6" (152mm), Length: 48" (1,219 mm)
Thickness	Overall: 0.1" (2.5mm) Wear Layer: 0.5 mm (20mil)
Profile	Micro-Bevel Edges
Coverage	Plank: 36 sq.ft (3.34 sq.m) per box
Planks per Box	Plank: 18 Planks
Weight	Plank: 39 lbs. (17.69 kg) per box
Composition	Luxury Vinyl Plank (LVP)
Туре	Glue Down
Application	Commercial & Residential
Surface Treatment	GrapheneX™ Protection
Finish	Embossed Wood Grain Pattern
Backing	Dry Back
Warranty	10 Year Limited Commercial 20 Year Limited Residential
Manufactured in	United States of America

PERFORMANCE

Classification	ASTM F1700 Class III Type B embossed surface		Resistance to Light	ASTM F1515	Meets
			Static Load Resistance	ASTM F970*	3000 psi
Thickness	ASTM F386	Meets	Fire Test Data – Flame Spread	ASTM E648	Meets
Wear Layer Thickness	ASTM F410	Meets	Fire Test Data – Smoke Evolution ASTM E662		Meets
Size	ASTM F2421	Meets	Fire Test Data – Wall Application ASTM E84		Meets
Squareness	ASTM F2421	Meets	Fire Test Data - Canada	CAN/ULC S-102.2	Flame Spread - 5
					Smoke Developed - 75
Residual Indentation	ASTM F1914	Meets	ADA Standards for Accessible Design		
Chemical Resistance	ASTM F925	Meets	Chapter 3, Section 302.1		Meets
Resistance to Heat	ASTM F1514	Meets	Dimensional Stability	Internal	Meets





















