



Flexiglass®

GRP multi surface overlay
System

TECHNICAL DATA SHEET

Flexiglass® Resin

Description:

Flexiglass® is a pre-promoted thixotropic styrene free polyester flexible resin designed specifically for overlay Roofing Applications.

Benefits:

- Styrene free
- High flex resin properties
- Overlay resin
- Rapid cure system

Application:

For full application instructions please download the Flexiglass® Installation Guide from our website: www.cromar.uk.com

Typical Properties:

Physical Data in Liquid State at 25°C:

Storage:

Resins are stable for six months from date of production when stored in the original containers away from sunlight at no more than 21°C. After extended storage, some drift may occur in gel time. During the hot summer months, no more than two months stability at 86°F/30°C should be anticipated.

Health & Safety:

Please refer to the Material Safety Data Sheet on Cromar Flexiglass® Resin. Always read and understand the Material Safety Data Sheet before working with this product.

Mechanical Data in the Cured State:

Test	Units of Measure	Nominal
Viscosity; Brookfield LV3 @ 60rpm	CPS	1500
Thixotropic Index; 6/60	-	2.5
Monomer Content	%	25
Gel Time; 100g 2.5% catalyst L40 LV	MINUTES	20
Peak Exotherm	°C	100



Further Information:

In the event of further queries or problems concerning the use of this product, please contact the address below, e-mail: info@cromar.uk.com or telephone our Technical Line on 01977 663 133 option 4. All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Cromar Building Products Limited products are available for sale in accordance with Cromar Building Products Limited standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.