

www.cedral.world

Cedral Slates

Accessories: Cedral Slate Trim 1 (ST1) for New Roofs

Product Code: IE SST1.BB.3050



Application

Installed on gable ends as a verge trim product with Cedral fibre cement slates, on new roofs.

Design

A cold formed coated aluminium component for use as a roofing product to I.S. EN 14783:2013. This trim permanently secures slates on gables to help prevent storm damage, along with an enamel finish making it resistant to all weather elements. This aluminium trim is flexible and easy to install allowing you to use it on all roof types.

3050mm long New Roofs Blue-Black Comply with BS5534

Essential Characteristics	Performance
Water Permeability	Water Impermeable
Dimensional Change	24 x 10 ⁻⁶ K ⁻¹
Water Vapour and Air Permeability	Air and Vapour Impermeable
Release of Dangerous Substances	Dangerous Substances Absent
External Fire Performance	Class B _{ROOF(t1)} , Class B _{ROOF(t2)} , Class B _{ROOF(t3)} , Class B _{ROOF(t4)}
Reaction to Fire	R _{TF} A1
Durability	Grade 3103 Aluminium sheet of 0.7mm thickness, coated with 2µm of PE – Alchydic backing coat and 19µm Polyester top coat.

Disclaimer

The information in this Technical Note is correct at time issuing. However, due to our committed program of continuous material and system development we reserve the right to amend or alter the information contained therein without prior notice. Please contact your local Etex Exteriors Sales Organization to ensure you have the most current version. All figures contained in this document are illustrations and should not be used as construction drawings. This information is supplied in good faith and no liability can be accepted for any loss or damage resulting from its use. This document is protected by international copyright laws. Reproduction and distribution in whole or in part without prior written permission is strictly prohibited. Cedral and logos are trademarks of Etex NV or an affiliate thereof. Any use without authorisation is strictly prohibited and may violate trademark laws.



TECHNICAL NOTE Cr-03/06/en/v2