

## UK Declaration of Performance

### Inno-Torch

1000.UKDoP.ETIT.001 1001.UKDoP.ETIT.001

Unique identification code of the product-type: **Inno-Torch**  
 Intended use/es: **Thermal insulation for buildings**  
 Manufacturer: **Kingspan Insulation Ltd, Herefordshire, HR6 9LA, UK**  
 System/s of AVCP: **System 4 (Reaction to fire), System 3 (Other Properties)**  
 Designated technical specification: **BS-EN 13165:2012+A2:2016**  
 UK Assessment/Notified body/ies: **University of Salford:1145, B.I.T.S: 1334, BBA: 0836**

| Essential characteristics   |   | Performance   |
|---|---|---|
| Thermal resistance  | Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)                                      | d <sub>N</sub> 30mm 1.10<br>d <sub>N</sub> 40mm 1.45<br>d <sub>N</sub> 50mm 1.85<br>d <sub>N</sub> 60mm 2.20<br>d <sub>N</sub> 70mm 2.55<br>d <sub>N</sub> 80mm 3.20<br>d <sub>N</sub> 90mm 3.60<br>d <sub>N</sub> 100mm 4.00<br>d <sub>N</sub> 120mm 5.00<br>d <sub>N</sub> 130mm 5.40<br>d <sub>N</sub> 140mm 5.83<br>d <sub>N</sub> 150mm 6.25 |
|   | Thermal conductivity $\lambda_D$ (W/(m.K))  | Flat board - Pembridge Plant 1000<br>d <sub>N</sub> < 80mm 0.027<br>d <sub>N</sub> 80-119mm 0.025<br>d <sub>N</sub> ≥ 120mm 0.024<br>Flat board – Selby Plant 1001<br>d <sub>N</sub> < 80mm 0.027<br>d <sub>N</sub> 80-119mm Not manufactured<br>d <sub>N</sub> ≥ 120mm 0.024   |
|   | Thickness tolerance   | T2  |
| Reaction to fire  | Reaction to fire  | F   |
| Durability of reaction to fire against heat, weathering, ageing / degradation | Durability of the reaction to fire of the product as placed on the market             | NPD   |
|   | Durability of thermal resistance and thermal conductivity against ageing/ degradation | NPD   |

## UK Declaration of Performance

### Inno-Torch

1000.UKDoP.ETIT.001 1001.UKDoP.ETIT.001

|   |  |   |
|---|--|---|
| Durability of Thermal Resistance against heat, weathering, ageing / degradation | Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)                         | Thermal resistance as table above   |
|   | Thermal conductivity $\lambda_D$ (W/(m.K))                               | Flat board - Pembridge Plant 1000<br><br>$d_N < 80\text{mm}$ 0.027<br>$d_N 80\text{-}119\text{mm}$ 0.025<br>$d_N \geq 120\text{mm}$ 0.024<br><br>Flat board – Selby Plant 1001<br><br>$d_N < 80\text{mm}$ 0.027<br>$d_N 80\text{-}119\text{mm}$ Not manufactured<br>$d_N \geq 120\text{mm}$ 0.024 |
|   | Durability characteristics   | NPD   |
|   | Dimensional stability under specified temperature and humidity condition | DS(70,90)3<br>DS(-20,-)1  |
|   | Deformation under specified compressive load and temperature conditions  | NPD   |
| Determination of the aged values of thermal resistance and thermal conductivity | $\lambda_D$ 0,024, 0.025,0,027W/m.K                                      |   |
| Compressive strength  | Compressive stress or compressive strength                               | CS(10Y)150  |

## UK Declaration of Performance

### Inno-Torch

1000.UKDoP.ETIT.001 1001.UKDoP.ETIT.001

|   |   |      |
|---|---|------|
| Tensile / Flexural strength                                     | Tensile strength perpendicular to faces | TR80 |
| Durability of compressive strength against ageing / degradation | Compressive creep                       | NPD  |
| Water permeability  | Short term water absorption             | NPD  |
|   | Long term water absorption              | NPD  |
|   | Flatness after one sided wetting        | NPD  |
| Water vapour permeability                                       | Water vapour transmission               | NPD  |
| Acoustic absorption index                                       | Sound absorption                        | NPD  |
| Continuous Glowing Combustion                                   | Glowing Combustion                      | NPD  |
| Release of dangerous substances to the indoor environment       | Release of dangerous substances         | NPD  |
| NPD: No Performance Determined                                  |   |      |

EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2020.)

Signed for and on behalf of the manufacturer by:



.....  
**Aiveen Kearney**  
**Managing Director**  
**Pembridge, Selby, England, UK**  
**Date signed: 03/07/2023**  
**Issue Number: 001**



## UK Declaration of Performance

Inno-Torch

1000.UKDoP.ETIT.001 1001.UKDoP.ETIT.001



For the most up-to-date version of the Declaration of Performance please scan or [click here](#).

To access pre-existing product information or information relating to previously sold/discontinued products please email [literature@kingspaninsulation.co.uk](mailto:literature@kingspaninsulation.co.uk)