Eurothane[®] Eurodeck

Eurothane Eurodeck is a thermal insulation board. Its core consists of rigid polyisocyanurate PIR foam. The board is faced with a gas diffusion tight multilayer foil on both sides.

Application(s)

Thermal insulation used in warm flat roofs. The board can be used in mechanical fixed waterproofing systems.

Board				
Description	Value	Unit	Tolerances	Standard
Dimensions				
Length	2400	mm		
	1200	mm		
	600	mm		
Width	1200	mm		
Thickness range	30 - 160	mm	T2	EN 823
Density (core volume weight)	± 30	kg/m³		
Appearance				
Facing	Gas diffusion tight multilayer on both sides			
Edge finishing	Straight edges			

Essential Characteristics				
Description	Standard	EN code	Value	Unit
Thermal conductivity (declared value)				
All thicknesses	EN 13165	λ _D	0.022	W/m.K
Mechanical properties				
Compressive stress or compressive strength at 10% deformation	EN 826	CS(10/ Y)150	≥150	kPa
Fire behaviour				
Reaction to fire (product as such)	EN 13501-1	Euroclasse	F	

Care has been taken to ensure that the content of this document is as accurate as possible. Please note that technical specifications may vary from country to country. Recticel Insulation does not accept any liability for clerical errors and reserves the right to amend information without prior notice. This document does not create, specify, modify or replace any new or prior contractual obligations agreed upon in writing between Recticel Insulation and the user.



1/2 191KUE8UQ4ND 201021

Recticel Insulation Enterprise Way, Whittle Road, Meir Park, Stoke-on-Trent, Staffordshire, ST3 7UN, UK

www.recticelinsulation.com

Eurothane[®] Eurodeck

Insulation Values		
Thickness (mm)	λ _D -value (W/mK)	R _D -value (m²K/W)
30	0.022	1.35
40	0.022	1.80
50	0.022	2.25
60	0.022	2.70
70	0.022	3.15
75	0.022	3.40
80	0.022	3.60
90	0.022	4.05
100	0.022	4.50
110	0.022	5.00
120	0.022	5.45
130	0.022	5.90
140	0.022	6.35
150	0.022	6.80
160	0.022	7.25

Standards & Certificates		
Standards		
Product standard	EN 13165:2012 + A2:2016	
Production	ISO 9001:2015	
Environmental management	ISO 14001:2015	
Certificates		
BBA	95/3113	(30-160mm)

Production plant	
Stoke-on-Trent	Enterprise Way, Meir Park, Stoke-on-Trent, ST3 7UN
Storage/handling	Stock dry and protected from direct sunlight

Care has been taken to ensure that the content of this document is as accurate as possible. Please note that technical specifications may vary from country to country. Recticel Insulation does not accept any liability for clerical errors and reserves the right to amend information without prior notice. This document does not create, specify, modify or replace any new or prior contractual obligations agreed upon in writing between Recticel Insulation and the user.

Recticel Insulation Enterprise Way, Whittle Road, Meir Park, Stoke-on-Trent, Staffordshire, ST3 7UN, UK



www.recticelinsulation.com