

# QuickSeam Splice Tape

## 1. Description

Firestone's 76 mm (3") and 152 mm (6") QuickSeam Splice Tape is designed for field splicing of RubberGard EPDM membrane panels.

## 2. Preparation

The RubberGard EPDM surfaces must be prepared with QuickPrime Plus, using a QuickScrubber or QuickScrubber Plus tool. Use of other products is not allowed. Restore the tape to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

## 3. Application

A 76 mm (3") wide tape is used for splicing standard seams without mechanical attachment in the seam. A 152 mm (6") wide tape is used for splicing seams with mechanical attachment centred within the seam. Refer to the Firestone installation guidelines for specific installation instructions.

## 4. Coverage

In accordance with length of seam. At end of the roll, overlap a minimum of 25 mm (1").

## 5. Characteristics

<b>Physical</b>	<ul style="list-style-type: none"><li>■ Excellent moisture resistance</li><li>■ Excellent resistance to heat and cold</li><li>■ Excellent green tack</li></ul>
<b>Technical</b>	<ul style="list-style-type: none"><li>■ Base Rubber polymers</li><li>■ Colour Black</li><li>■ Solvents None</li><li>■ Solids (%) 100</li><li>■ State Cured</li><li>■ Thickness 0.76 mm ± 0.127 mm</li></ul>

## 6. Packaging / Storage / Shelf Life

Width (mm)	Length (m)	Packaging
76 (3")	30.5 (100')	6 rolls/carton
152 (6")	30.5 (100')	2 rolls/carton

*Note: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.*

**Storage:** Store in original unopened containers at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

**Shelf Life:** 12 months can be expected if stored in above-mentioned conditions. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories. Quality and applicability should thus always be verified: QuickSeam Tape can be used only as long as the release paper can easily be removed from the tape without tearing the paper apart.

## 7. Precautions

Refer to Material Safety Data Sheets.

