

## QuickSeam™ FormFlash™ 18"



### 1. Description

The Firestone QuickSeam™ FormFlash™ 18" is a 450 mm wide uncured EPDM strip factory-laminated to QuickSeam Tape. It has a polyester release liner for easy removal and excellent weather resistance. The QuickSeam FormFlash 18" can be used to carry out general roof repairs and flash in drain insert pieces.

### 2. Preparation

The RubberCover™ EPDM surfaces and/or mating surfaces must be prepared with QuickPrime™ Plus, using a QuickScrubber™ or QuickScrubber™ Plus tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

### 3. Application

On cloudy days with ambient temperature below 15°C, the use of a heat gun is recommended to warm the QuickSeam FormFlash and to ensure good formability. On sunny days, pre-heating of the product is usually not necessary. QuickSeam FormFlash is to be applied as per the Firestone specifications and details.

### 4. Coverage

In accordance with length of detail.

### 5. Characteristics

| Technical   |               |                 |
|-------------|---------------|-----------------|
|             | EPDM Flashing | QuickSeam Tape  |
| • Base      | EPDM          | Rubber polymers |
| • Color     | Black         | Black           |
| • Solvents  | None          | None            |
| • Solids    | 100%          | 100%            |
| • State     | Uncured       | Cured           |
| • Thickness | 1.6 mm        | 0.6 mm          |
| • Width     | 450 mm        | 456 mm          |

### 6. Packaging / Storage / Shelf Life

|             |  |
|-------------|--|
| Packaging   | 15.2 m (50') rolls - 1 roll per carton |
| Part number | W56RAC162A                             |

*Note: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.*

**Storage:** Store in original unopened containers at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

**Shelf Life:** 12 months, when stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures.

### 7. Precautions

Refer to Safety Data Sheets.