

## QuickSeam™ Corner Flashing

### 1. Description

The Firestone QuickSeam™ Corner Flashing is a 216 mm in diameter round piece of uncured EPDM FormFlash laminated to QuickSeam Tape. It is designed to flash outside corners or to be used as a cover patch where appropriate.



### 2. Preparation

The RubberCover™ EPDM surfaces and/or mating surfaces must be prepared with QuickPrime™ Plus, using a QuickScrubber™ tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

### 3. Application

On cold days with ambient temperature below 5°C, the use of a heat gun is recommended to warm the QuickSeam Corner Flashing and to ensure good formability. On normal days, pre-heating of the product is not necessary.

### 4. Coverage

One piece per corner.

### 5. Characteristics

Technical	EPDM Flashing	QuickSeam Tape
• Base	EPDM	Rubber polymers
• Color	Black	Black
• Solvents	None	None
• Solids	100 %	100 %
• State	Uncured	Cured
• Thickness	1.6 mm	0.6 mm
• Width	216 mm	216 mm

### 6. Packaging/ Storage/ Shelf Life

Packaging	20 pieces per carton
Part number	W56RAC1646

**Storage:** Store in original unopened containers at temperatures between 15°C and 25°C. Keep the material out of direct sunlight until ready for application.

**Shelf Life:** 12 months can be expected if stored in above-mentioned conditions. Shelf life will be reduced if exposed to higher temperatures.

### 7. Precautions

Refer to Safety Data Sheet.