



SAFETY DATA SHEET

Grassflex Rubber Tiles

PRODUCT AND COMPANY IDENTIFICATION

Product type:	Artificial Grass Topped Rubber Tiles
Trade Name:	"Grassflex"
Manufacturer:	Castle Composites Limited Units 1-5, Nisbet Way Ravenstruther Lanark, ML11 7SF
Phone No.:	01555 870003
Fax No.:	01555 870040

Packing Information

Stacked on wooden pallets with shrink wrap.
Interlocking pins contained within a bag at the top of each pallet

Product Information

Composition: Recycled Rubber Granulate bound using poly urethane binding agent with artificial grass top.

Size: 500x500x25mm
500x500x30mm
1000x1000x25mm

Density: 800kg/m³

Fire Resistance: EFL to EN 13501

Smoke Resistance: S2

Size Tolerance: Width 2%, Thickness 5%

Guarantee: 3 Years for wear resistance, provided the product is used for roof terraces or balconies. The guarantee does not apply to colour.

Insulation Value: Rd 0,15 EN13165, U 3,13 EN6946

Water Permeability: 250mm Per Hour EN12616

Maintenance: Artificial grass top will need to be swept up on occasion to maintain the pile height. Frequency of this process will depend on the amount of foot traffic the tiles receive.