

Printing date 12.01.2022 Vers.No.: 10 Revision: PJ0822RR

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

-1.1 Product identifier

Trade name: Rapid Pro Detailer

- Article number: LRS RapidRoof Det

 1.2 Relevant identified uses of the substance or mixture and uses advised against Unsuitable for home DIY applications.

- Application of the substance / the preparation: Reaction resin
- -1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

**LRS** 

Prees Green SY13 2BN

Tel.: 01948841877

e-mail:info@lrs-systems.co.uk

- Further information obtainable from: Environmental department
- **1.4 Emergency telephone number:** 07983631893 or contact NHS 111/a doctor

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





**GHS02 GHS07** 

- · Signal word Danger
- · Hazard-determining components of labelling:

n-butyl acrylate
methyl methacrylate
Triothylogo glycol dimethacryl

Triethylene glycol dimethacrylate

· Hazard statements

H225 Highly flammable liquid and wapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

(Contd. on page 2)

Printing date 12.01.2022 Vers.No.: 10 Revision: PJ0822RR

Trade name: Rapid Pro Detailer

Precautionary statements

(Contd. of page 1)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information:

Safety data sheet available on request.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

- 3.2 Chemical characterisation: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural substance with a Community workplace exposure limit	25-50%
CAS: 141-32-2 EINECS: 205-480-7 Reg.nr.: 01-2119453155-43- xxxx	n-butyl acrylate  Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	10-25%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate  Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	10-25%
CAS: 109-16-0 EINECS: 203-652-6 Reg.nr.: 01-2119969287-21	Triethylene glycol dimethacrylate  Skin Sens. 1B, H317	0.5-2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air and to be sure call for a doctor.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:
- Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB

Printing date 12.01.2022 Vers.No.: 10 Revision: PJ0822RR

Trade name: Rapid Pro Detailer

(Contd. of page 2)

### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Foam

Sand

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- -5.2 Special hazards arising from the substance or mixture

Exothermic polymerisation.

In case of fire, the following can be released:

Hydrocarbons

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

- -5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.
- Additional information Cool endangered receptacles with water spray.

#### **SECTION 6: Accidental release measures**

#### · 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in cool, dry conditions in well sealed receptacles.

Do not allow to enter sewers/ surface or ground water.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

- Maximum storage temperature: 25°C
- 7.3 Specific end use(s) No further relevant information available.

<del>CB</del>

Printing date 12.01.2022 Vers.No.: 10 Revision: PJ0822RR

Trade name: Rapid Pro Detailer

(Contd. of page 3)

#### **SECTION 8: Exposure controls/personal protection**

- 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:
7707 40 7 b a s'anna a a la b a ta a sa tama l

### 7727-43-7 barium sulphate, natural

WEL Long-term value: 10\* 4\*\* mg/m³ \*inhalable dust \*\*respirable dust

#### 141-32-2 n-butyl acrylate

WEL Short-term value: 26 mg/m³, 5 ppm Long-term value: 5 mg/m³, 1 ppm

#### 80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

- Additional Information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection:

Use the indicated respiratory protection if workplace exposure limits are exceeded.

- Recommended filter device for short term use: Filter A
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (EN 374)

- Material of gloves Butyl rubber, BR
- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 3).

Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

#### **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
- General Information
- Appearance:

Form: Fluid

(Contd. on page 5)

Printing date 12.01.2022 Vers.No.: 10 Revision: PJ0822RR

Trade name: Rapid Pro Detailer

	(Contd. of page
Colour:	Different according to colouring
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Mixture is non-soluble (in water).
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	
· Flash point:	10 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	245 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	12.5 Vol %
· Vapour pressure at 20 °C:	38.7 hPa
· Density at 20 °C:	1.35 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	12,000 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
· 9.2 Other information	No further relevant information available.

### **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

Keep away from heat and direct sunlight.

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Exothermic polymerisation.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Reacts with peroxides and other radical forming substances.
- 10.6 Hazardous decomposition products:

Hydrocarbons

Carbon monoxide and carbon dioxide

· Additional information: Do not allow to enter sewers/ surface or ground water.

Printing date 12.01.2022 Vers.No.: 10 Revision: PJ0822RR

Trade name: Rapid Pro Detailer

(Contd. of page 5)

### **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- -13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Must be specially treated adhering to official regulations.

- Uncleaned packaging:
- Recommendation:

Packaging may be reused or recycled after cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Disposal must be made according to official regulations.

Recommended cleansing agents: Acetone, ethylacetate

GB

Printing date 12.01.2022 Vers.No.: 10 Revision: PJ0822RR

Trade name: Rapid Pro Detailer

(Contd. of page 6)

SECTION 14: Transport information
-----------------------------------

• 14.1 UN-Number • ADR, IMDG, IATA UN1866

· 14.2 UN proper shipping name

- ADR 1866 RESIN SOLUTION RESIN SOLUTION

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



• Class 3 Flammable liquids.

· Label

· 14.4 Packing group

- ADR, IMDG, IATA

· 14.5 Environmental hazards:

- Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 33
 EMS Number: F-E,S-E
 Stowage Category B

· 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

• Transport category

• Tunnel restriction code D/E

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 Code: Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

• UN "Model Regulation": UN 1866 RESIN SOLUTION, 3, II

#### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000t

(Contd. on page 8)

Printing date 12.01.2022 Vers.No.: 10 Revision: PJ0822RR

Trade name: Rapid Pro Detailer

(Contd. of page 7)

- · National regulations:
- · Technical instructions (air):

Class	Share in %
ı	≤ 2,5
NK	10-25

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

- Department issuing SDS: Environmental Department

#### Abbreviations and acronyms:

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.