

Technical Data – Lindum	
Minimum roof pitch*	22.5° smoothfaced 30° sandfaced
Headlap (minimum)	75 mm
Headlap (maximum)	120 mm
Batten spacing at maximum gauge	345 mm
Batten spacing at minimum gauge	300 mm
Size of tile	420 x 334 mm
Covering capacity at maximum gauge	9.7 tiles per m ²
Cover width	300 mm
Profile depth	42 mm
Hanging length	401 mm
Weight as laid	45.6 kg per m ²
Weight per 1000 (including pallet & packaging)	4.708 tonnes
Weight per tile	4.65 kg
Weight per pallet (including pallet & packaging)	1.017 tonnes
Quantity per pallet	216
Battens per m ²	2.9 m
Batten size - up to 450 mm rafter centres	38 x 25mm
Batten size - up to 600 mm rafter centres	50 x 25mm
Nail size/type for tiles	50 x 3.35 mm aluminium ring shank clout head
Nail size/type for metal tile clips	55 x 3.35 mm aluminium ring shank clout head

Product specification is subject to change and will be updated accordingly. Unless otherwise stated, data is based on the tiles laid at minimum headlap.

Before deciding on the batten gauge and linear coverage, the roof tiler should inspect each batch of tiles to ensure that the correct minimum headlap and sidelap are achieved. For further guidance, download the [Lindum Installation Guide](#).

Tile Fixing

Sandtoft roof tiles must be laid and fixed to comply with BS 5534: the British Standard Code of practice for slating and tiling, and BS 8000: Part 6: the British Standard Code of practice for workmanship on building sites.

To ensure compliance with these Standards we strongly recommend that a calculated fixing specification be obtained from Sandtoft Technical Support or using Sandtoft's online FixSPEC tool at www.wienerberger.co.uk or www.roofspec.co.uk

For further information go to www.wienerberger.co.uk or contact Sandtoft Technical Support on 0844 9395 999.