

# TIXAL

## THIXOTROPIC ADDITIVE FOR ULTRAFLEX MEMBRANE

Tixal is a polymeric thickener, it has been especially developed as a liquid additive for the polyurethane liquid membrane ULTRAFLEX, to use on vertical or sloped surfaces, giving thixotropic properties.

### USES

- Additive for the membrane ULTRAFLEX, to apply on vertical or sloped surfaces.
- Prevent slump of the membrane due to its drying time.

**NOTE:** call our technical department about the application to other supports or situations.

maximum consumption

500 m l per 15 kg of ULTRAFLEX

### APPLICATION METHOD

Add Tixal in the proportion required (maximum 500 ml per 15 kg of ULTRAFLEX) in the drum of the membrane mix continuously until a homogeneous product is achieved apply the mixture by short hair solvent resistant roller if the environmental temperature is lower than 5 °C , heat before mix with ULTRAFLEX.

### SHELF LIFE

12 months at temperatures between 5° C and 35° C, provided it is stored in a dry place.

### PACKAGING

Metal tins of 1l.

### HANDLING

These safety recommendations for handling, are necessary for the implementation process as well as in the pre-and post, on exposure to the loading machinery.

- Respiratory Protection: When handling or spraying use an air purifying respirator.
- Skin protection: Use rubber gloves, remove immediately after contamination. Wear clean body covering. Wash thoroughly with soap and water after work and before eating, drinking or smoking.
- Eye / Face: Wear safety goggles to prevent splashing and exposure to particles in air.
- Waste generation should be avoided or minimized. Incinerate under controlled conditions in accordance with local laws and national regulations.

Consult the material and safety data sheet of the product (MSDS), or contact our technical department.