



## Wakaflex is an outstanding lead free alternative to conventional lead flashing.

Wakaflex is a non toxic flexible, self-adhesive flashing designed to replace lead in most modern roofing applications. This lead alternative can be stretched over details whilst dressing to give a smoother and neater finish. Wakaflex stretches up to 50% in length and 15% in width when dressed into the pan of the tile.



### Features and benefits

- Stretches up to 50% in length and 15% in width when dressed into the pan of the tile, ensuring easy application for a wide range of details.
- Unique product composition allows self-welding of laps.
- Non toxic material has the appearance of lead with no scrap value.
- Perforated release paper allows easy application.
- Premium product offering a genuine alternative to lead.

### Area of application

- Step or cover flashing at wall or chimney abutments.
- Top edge abutment detail.
- Saddle detail.
- Valleys.
- Suitable for new build and refurbishments.

### Related products

- Flashing Roller PACCRO
- Flashing Sealant PACCSE
- Flashing Glue PACCGL\*

### Approvals and certifications

- BBA Certificate 14/5103
- 20 year guarantee against manufacturing defect.



\* Recommended to help fix the butyl strip in damp conditions.

### Technical guidance

Material	Polyisobutylene (PIB) with aluminium mesh work and butyl-adhesive tape.
Installation temperature	Minimum 5°C
Temperature resistance	-20°C to +80°C
Thickness	2 mm
UV Stability	UV stable
Butyl adhesive	Should be applied to suitable surfaces only, which are dry and dust free. Not suitable for use with bituminous roof coverings.
Fire Rating	B2 (DIN4102-1:1998)
Sealant	Flashing Sealant PACCSE should be used for brickwork joints. Under no circumstances should silicone based sealants or adhesives be used.
More information	Please refer to installation guide for further guidance.

### Product information

Product code	Width mm	Length m	Weight kg	Colour	Box quantity	Pallet quantity
PWF140GR	140	5	2.84	Light Grey	2	96
PWF180GR	180		3.55	Light Grey	4	84
PWF280AN	280		5.2	Anthracite		84
PWF280GR		Light Grey	2	42		
PWF280GR-10	10	10.48			Light Grey	
PWF370AN	370	5	6.8	Anthracite	3	48
PWF370GR				Light Grey		
PWF560AN	560		10.4	10.4	Anthracite	2
PWF560GR		Light Grey				

Klober is certified to ISO 9001:2015 for Quality Management and ISO 14001:2015 for Environmental Management. All Klober products comply fully with all relevant Building Regulations and British Standards.