

## QuickPrime™ Plus

### 1. Description

The Firestone QuickPrime™ Plus is designed to clean and prime the RubberCover™ EPDM membrane and/or substrate before the application of a QuickSeam™ product. QuickPrime Plus must be applied with a QuickScrubber™ pad and handle.



### 2. Preparation

Surfaces to be primed must be clean, dry and free of foreign materials, talc and dirt. Pre-cleaning may be required. Stir QuickPrime Plus thoroughly before and during use. When exposed to lower temperatures for a prolonged period of time, restore to room temperature prior to use. Pour the required amount of QuickPrime Plus into a bucket for ease of application.

### 3. Application

Apply QuickPrime Plus to the RubberCover EPDM surfaces and/or other substrates to receive QuickSeam products with the QuickScrubber pad and handle, using long back and forth strokes with moderate to heavy pressure along the length of the area until surfaces become dark grey, with no streaking or puddling. Allow the primed surfaces to dry completely (usually less than 10 minutes) before applying a QuickSeam product.

### 4. Coverage

Thinning is not allowed. The following rates can be achieved with 1 can (0.95 l):

- QuickSeam SA Flashing: 8 lm - 1 side.
- QuickSeam Corner Flashing: 50 pieces - 1 side.
- QuickSeam Cover Strip: 20 lm - 1 side.

### 5. Characteristics

| Technical          |                           |
|--------------------|---------------------------|
| • Base             | Synthetic rubber polymers |
| • Color            | Translucent grey          |
| • Solvents         | Heptane, toluene          |
| • Solids           | 16 % - 18 %               |
| • Viscosity        | Very thin, free-flowing   |
| • Specific gravity | 0.793 (Water = 1)         |
| • Flash point      | -17.8°C                   |

### 6. Packaging/ Storage/ Shelf Life

|             |   |
|-------------|---|
| Packaging   | 0.95 l (¼ US gallon) pail – 12 pails per carton |
| Part Number | W56RAC1695                                      |

**Storage:** Store in original unopened containers at temperatures between 15°C and 25°C until ready for use. Keep the material out of direct sunlight until ready for application.

**Shelf life:** 12 months can be expected if stored in above-mentioned conditions. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories. Quality and applicability should thus always be verified: when mixed, product should stir into a smooth and homogeneous blend with no evidence of major clumping or separation/phasing.

# Technical Information Sheet

---



## 7. Precautions

Refer to Safety Data Sheet (SDS). Flammable. Keep away from fire and open flame and other possible ignition sources during storage and use. Do not smoke when using. Use only in well ventilated areas. Avoid contact with skin and eyes. For professional use only. Keep out of reach of children.