



Technical Detail

Latii, Architectural Aluminum Line, i282

Energy Efficiency

Please consult typology, dimensions and glazing.

Thermal Transmission Coefficient: $U_w \geq 0.83$ (W/m²K)

Acoustic Insulation

Maximum glazing: 54 mm

Maximum acoustic insulation: $R_w = 56$ dB

Categories Archived at Test Center

Protection against atmospheric agents

Air permeability (EN 12207): Class 4

Water tightness (EN 12208): Class E1200

Wind resistance (EN 12210): Class C5

Reference test 1.23 x 1.48 m / 2 Sashes

Jamb Depth	Classic Frame 100 mm Modern Frame 70 mm Sash 83 mm
------------	--

Thickness	72.5 mm Sash + Frame
-----------	----------------------

Maximum Dimensions	Width (L) = 1.500 mm Height (H) = 2.600 mm
--------------------	---

Maximum Weight / Sash	160 Kg
-----------------------	--------

Please consult maximum dimensions according to types.

Finishes	Powder Coating RAL Powder Coating Wood Effect Powder Coating/Textured Powder Coating/Site Anodized Anti-Bacterial Powder Coating Available
----------	---

Hardware	Optionally concealed hinges Optionally security hardware
----------	---

Extrusion Alloy	6063 T-5
-----------------	----------

Polyamide Strip Length	Polyamide 6.6 reinforced with 25% fiberglass: 32 - 39 mm
------------------------	--

Gaskets	EPDM triple gasket
---------	--------------------

Opening Possibilities	
Inward	Side hung, tilt and turn&tilt
Outward	Side hung