# Chatillon<sup>®</sup> PDT Series Bench Scales

Specification Sheet SS-PDT-0310 March 2010

The CHATILLON® PDT Series floor platform scale features a large, easy-to-read 13-inch (330 mm) dial with knife-edge pointer for accurate measurements. The PDT Series is a Class III "Legal for Trade" scale. Scales feature a large 17 x 12-inch (430 x 305 mm) steel platform. Designed for floor use, the PDT features a rugged cast-iron base with heavy-gauge steel platform for excellent stability. The scale's mounting feet are adjustable. Options include a stainless steel platform and quick tare knob. Tare adjustments may be made up to 10% of rated capacity. The scale's head cover and column back are removable for easy access to the dial mechanism and the dashpot. Scale is assembled on-site with standard tools. Assembly does not affect calibration.

## **Features**

- H44 Class III "Legal for Trade"
- Avoirdupois and Metric Dials
- 13-inch (330mm) Reading Dial with Knife-edge Pointer
- Full Scale in 1 Revolution
- Rugged Cast Iron Base, Heavy-gauge Steel Construction
- 1 Year Warranty

## **Specifications**

Accuracy: See Ordering Safe Overload: 120% of rated capacity Ultimate Overload: 125% of Rated Capacity Display: Single Reading Operating Temperature: 45° to 104°F (7° to 40°C) Storage Temperature: -4° to 104°F (-20° to 40°C) Instrument Weights: 50 lbs (23 kg) Shipping Weight: 60 lbs (28 kg)

Note: Weights are approximate.







Visit us on the worldwide web: www.chatillon.com



# Ordering

Accuracies - Class III "Legal for Trade"

Model	Resolution	Range	Scale Divisions	Tolerance		
				Division	Weight	%Accurate
PDT-065	65 lb x 2 oz	0 - 62 lb	0 - 500	<u>+</u> 1/2 d	<u>+</u> 1 oz	<u>+</u> 0.10%
		63 - 65 lb	501 - 2000	<u>+</u> 1 d	<u>+</u> 2 oz	<u>+</u> 0.19%
PDT-130	130 lb x 4 oz	0 - 125 lb	0 - 500	<u>+</u> 1/2 d	<u>+</u> 2 oz	<u>+</u> 0.10%
		126 - 130 lb	501 - 2000	<u>+</u> 1 d	<u>+</u> 4 oz	<u>+</u> 0.19%
PDT-260	260 lb x 8 oz	0 - 250 lb	0 - 500	<u>+</u> 1/2 d	<u>+</u> 4oz	<u>+</u> 0.10%
		251 - 260 lb	501 - 2000	+1 d	+8 oz	+0.19%

Certificate of Conformance No. 90-078 was issued under the National Type Evaluation Program of the National Conference on Weights and Measures, that the design conforms to NIST Handbook 44 Class III. The scale is "Legal for Trade" subject to on-site verification by the local Weights and Measures jurisdictions.

#### 33-

**Dimensions** 


# Accessories

Part No.	Description
12130-3	Quick Tare Knob
16012	Stainless Steel Platform Cover
23019	Stainless Steel Provision Pan
16005-A	Damping Oil (65 lb, 130 lb, 25 kg, 50 kg)
16005-B	Damping Oil (260 lb, 520 lb, 100 kg, 200 kg)

#### Notes:

The provision pan weighs approximately 10 lbs. Scales with capacities less than 100 lbs must be back-started.

The Quick Tare Knob cannot be used on Legal for Trade applications.





### **MEASUREMENT & CALIBRATION TECHNOLOGIES**

Americas AMETEK Measurement & Calibration Technologies 8600 Somerset Drive Largo, Florida 33773 United States of America Tel +1-727-536-7831 Tel +1-800-527-9999 Fax +1-727-539-6882 Email challon.fl-lar@ametek.com 
 United Kingdom

 Lloyd Instruments Ltd.

 Steyning Way

 Bognor Regis

 West Sussex

 PO22 9ST

 United Kingdom

 Tel
 +44 (0) 1243 833 370

 Fax
 +44 (0) 1243 833 401

 Email uk-far.general@ametek.co.uk

France AMETEK S.A.S. Rond Point de l'Epine des Champs Buro Plus - Bat. D 78990 Elancourt France Tel +33 (0)1 30 68 89 40 Fax +33 (0)1 30 68 89 49 Email general@lloyd-instruments.com 
 Germany

 AMETEK GmbH

 Rudolf-Diesel-Strasse 16

 D-40670 Meebusch

 Germany

 Tel
 +49 (0) 2159 9136-70

 Fax
 +49 (0) 2159 9136-39

 Email info@ametek.de

 Singapore

 AMETEK Singapore Pvt. Ltd.

 10 Ang Mo Kio Street 65

 #05-12 Techpoint

 Singapore 569059

 Tel +65-6481-6588

 Email aspl@ametek.com.sg

For the authorized Chatillon Distributor or Manufacturer's Representative near you, go to www.chatillon.com

ISO 9001/2000 ISO/IEC17025 Manufacturer

Visit Us on the Worldwide Web at: www.chatillon.com © 2010 by AMETEK, Inc. Information within this document is subject to change without notice.