



Wall Mount Lighting Position Guide


*Wall mount fixtures for EVERY mounting
height and EVERY application*

- Energy efficient, easy contractor-friendly lighting solutions
- Lightweight designs allow for minimal installation effort
- Form factor and lumen packages for every opportunity


OPS WM



XWS/XWM




GST/GSR/GSQ




WPSLS/WPSLL



T_WP



SSA/SMA



OSP WM
3,000 - 14,000L





XWM
3,000 - 21,000L



XWS
1,000 - 8,000L



GST/GSR/GSQ
2,000 - 8,000L



WPSLS/WPSLL
2,000 - 8,000L





WPSLS/WPSLL
2,000 - 13,000L



SSA/SMA
12,000 - 48,000L



Wall Mount Lighting Position Guide

							
	★★★★★	★★★★★	★★★★★	★★★	★★★	★★★	★★★
Markets	Grocery & Pharmacy, Parking Lot/ Garage, Petroleum, QSR, Retail	Automotive, Grocery & Pharmacy, Parking Lot/Garage, Petroleum, QSR, Retail, Sports, Warehouse	Automotive, Grocery & Pharmacy, Parking Lot/Garage, Petroleum, QSR, Retail, Sports, Warehouse	Grocery & Pharmacy, Parking Lot/ Garage, Petroleum, QSR, Retail	Grocery & Pharmacy, Parking Lot/ Garage, Petroleum, QSR, Warehouse	Grocery & Pharmacy, Parking Lot/ Garage, Petroleum, QSR, Warehouse	Grocery & Pharmacy, Parking Lot/ Garage, Petroleum, QSR, Warehouse
Size L x W x H (in.)	18 x 16 x 4	8 x 13 x 5.5	13 x 20 x 5.5	17 x 7 x 9 / 18 x 7 x 9 / 18 x 9 x 9	4 x 6 x 7.5 / 5 x 9 x 9	Varies	19 x 13 x 3.5 / 22 x 13 x 3.5
Weight (lbs)	16	10	27	15	4 / 8	6 - 15	17 / 19
Typical Mounting Height (ft)	10 - 20	8 - 15	10 - 25	8 - 15	8 - 15	8 - 20	15 - 30
Surface Conduit Entry	Accessory Wiring Box	Extended Housing	Accessory Wiring Box	Accessory Wiring Box	Standard	Standard	Accessory Wiring Box
High Voltage (347-480V)	Yes	Yes	Yes	No	Yes	Yes	No
Lumen Package (lm)	3,000 - 14,000*	1,000 - 8,000*	3,000 - 21,000*	2,000 - 8,000	2,000 - 8,000	2,000 - 13,000	12,000 - 48,000
LPW Range	125 - 165	126 - 162	125 - 158	108 - 133	98 - 130	106 - 135	135 - 148
Lens/Optics	Acrylic (PC Option)	Silicone, PC or Acrylic	One Piece Silicone	Glass	Glass	Glass	Polycarbonate
Distributions	Type 3W, 4F, 5C, 5R, 5D, AD	Type 2, 3, FT	Type 2, 3, FT, 4	Forward Throw	Forward Throw	Forward Throw	Type 3, FT
Standard CCT/CRI	27K8, 30K8, 35K8, 40K8, 50K8	30K7, 40K7, 50K7	30K7, 40K7, 50K7	30K7, 40K7, 50K7	30K7, 40K7, 50K7	30K7, 40K7, 50K7	40K7, 50K7
Special CCT/CRI	AMB, AMT	AMB, AMT, 80CRI	AMB, AMT, 80CRI	27K8, 30K8, 35K8, 40K8, 50K8	45K7	45K7	-
IP Rating	IP66	IP65	IP65	Wet Location Rated	Wet Location Rated	Wet Location Rated	IP65
DLC*	Premium	Premium	Premium	Premium & Standard	Standard	Standard (TLWP 5L/11L)	Premium
Paint Finishes	LSI Standard + Custom Colors	LSI Standard + Custom Colors	LSI Standard + Custom Colors	Bronze, Black, Silver or White	Bronze, Black, Silver or White	Bronze, Black, Silver or White	Bronze Only
Photocell	Twist Lock	Button	Button	Button	Button	Button	Button or Twist Lock
Sensors & Wireless Controls	IMSBT, AirLink Blue	IMSBT, AirLink Blue	IMSBT, AirLink Blue, AirLink Synapse	IMSBT, AirLink Blue	-	-	IMSBT, AirLink Blue
7-Pin Receptacle	Yes	No	No	No	No	No	Yes
Surge Device	Optional	Optional	Optional	Optional	Optional	Optional	Optional
BAA	Yes	Yes	Yes	Select Configurations	Yes	Yes	No
Pricing (per lumen)	\$\$\$	\$\$	\$\$	\$\$	\$	\$	\$

*Custom lumen and wattage packages available, consult factory

**Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.



LSI Industries Inc. 10000 Alliance Rd. Cincinnati, OH 45242 • www.lsicorp.com
(800) 436-7800 • ©LSI Industries Inc. All Rights Reserved. Specifications subject to change without notice.

SELL.1102.E.0325