



## TECHNICAL DATA

### Air Tool Oil

Air Tool Oil has been specifically designed and formulated for use with all piston and rotary type air tools.

The special sulphurised fatty ester additives give a lubricant with minimum sulphur corrosivity together with maximum lubricating value and load carrying capacity. It is eminently suitable for both ferrous and non-ferrous metals. It lubricates, cleans and protects the air tool to which it is applied.

Tool life may be dramatically extended by the removal of gum deposits by Air Tool Oil, and improved power and speed is also provided.

### Features

- Provides improved air tool performance
- Lubricates, cleans and protects
- Removes gummy deposits
- Stops and inhibits rust
- Extends air tool life

### Applications

Impact wrenches	Tampers	Paving breakers
Ratchet wrenches	Hammers	Air pullers
Polishers	Drills	Screwdrivers
Chisels	Grinders	Etc

### Typical Physical Characteristics

Density at 15 C	0.899
Viscosity at 40 C	23.1cSt
Appearance	Clear green liquid
Product Code	08041

Rev:C/10



FM 10665

Specialised Welding Products Ltd

Unit 1, Farringdon Industrial Centre, Farringdon, Nr Alton, Hampshire GU34 3DD, UK tel: +44 (0)1420 588180 fax: +44 (0)1420 588184 email: sales@swp.uk.net

[www.specialisedwelding.co.uk](http://www.specialisedwelding.co.uk)