



## PENETRANT

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### PRODUCT NAME: PENETRANT

**SUPPLIER** Specialised Welding Products Ltd  
Unit 1 Farringdon Industrial Centre,  
Farringdon,  
Nr. Alton  
Hampshire,  
GU34 3DD

T (01420) 588180  
F (01420) 588184  
Email: Sales@swp.uk.net

Container size 400ml

### 2 HAZARDS IDENTIFIED

#### PHYSICAL AND CHEMICAL HAZARDS

**Extremely flammable. Irritating to skin. Vapours may cause drowsiness or dizziness.**

#### ENVIRONMENTAL HAZARDS

Toxic to the aquatic environment.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
Butane	203-448-7	106-97-8	20-30%	R12
Propane	200-827-9	74-98-6	20-30%	R12
Naphtha (petroleum) hydrotreated light	265-151-9	64742-49-0	20-30%	F; R11 Xi; R38 N; R51/53, R65, R67
Propan-2-one	200-662-2	67-64-1	10-20%	R11, R36, R66, R67
Propan-2-ol	200-661-7	67-63-0	5-10%	F; R11, Xi; R36, R67
Alcohol Ethoxylate	--	--	<5%	N; R52/53
Mineral Oil	232-455-8	8042-47-5	<5%	--
Pigment	--	--	<1%	--

The Full Text for all R-Phrases are displayed in Section 16

### 4 FIRST AID MEASURES

#### GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### INHALATION

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

#### INGESTION

**DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS!** If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Drink plenty of water. Get medical attention immediately. Provide rest and, warmth and fresh air.

#### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention promptly if symptoms occur after washing.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

**PENETRANT****5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Fire can be extinguished using: Foam, Carbon Dioxide (CO<sub>2</sub>), Dry Powder. DO NOT USE water jet.

**SPECIFIC HAZARDS**

Fire may produce dense black smoke containing hazardous combustion products (see Section 10). Decomposition products may be a hazard to health. Do not allow run-off from fire fighting to enter drains or water courses.

**PROTECTIVE MEASURES IN FIRE**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Avoid discharge into drains, water courses or onto the ground.

DO NOT allow to enter drains or watercourses. If the product enters drains or sewers, the local water company should be informed immediately. In the case of contamination of streams, rivers or lakes, inform the relevant environment Agency. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixture with air.

**SPILL CLEAN UP METHODS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage with non-combustible, absorbent material. Collect spillage in containers, seal securely and deliver for disposal accordingly to local regulations. Do not contaminate water sources or sewer.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Do not use sparking tools around aerosols. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours and spray mist, for personal protection, see Section 8. Use approved respirator if air contamination is above accepted level. Never apply pressure to the aerosol as it is a pressurised object and may explode if pressure is applied.

**STORAGE PRECAUTIONS**

Observe label precautions. Store between 5-25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Store separately from oxidising agents and strongly alkaline/acidic materials.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA – 8hrs	STEL – 15mins	Notes
Butane	WEL	1450 mg m <sup>-3</sup>	1810 mg m <sup>-3</sup>	
Naphtha (petroleum) hydrotreated light				No data
Propan-2-one	WEL	1210 mg m <sup>-3</sup>	3620 mg m <sup>-3</sup>	
Propan-2-ol	WEL	999 mg m <sup>-3</sup>	1250 mg m <sup>-3</sup>	

WEL = Workplace Exposure Limit

**PROTECTIVE EQUIPMENT**

**PENETRANT****8 EXPOSURE CONTROLS/PERSONAL PROTECTION - CONTINUED****ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided. Wear mask supplied with: Gas cartridges suitable for organic substances.

**HAND PROTECTION**

Use protective gloves.

**EYE PROTECTION**

Wear approved safety goggles.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station.

**HYGIENE MEASURES**

**DO NOT SMOKE IN WORK AREA.** Wash at the end of each shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

FORM:	Aerosol
FLASHPOINT:	Not known for blend
COLOUR:	Red
ODOUR:	Naphtha/ Acetone

**10 STABILITY AND REACTIVITY**

STABILITY:	Stable under the recommended storage and handling conditions in Section 7.
CONDITIONS TO AVOID:	Applying heat or pressure to the aerosol may result in explosion And fire. Naked flames, smoking, wet and damp storage conditions and mishandling may also result in explosion and fire.
MATERIALS TO AVOID: materials	Keep away from oxidising agents, strong alkaline/acidic
HAZARDOUS DECOMPOSITION PRODUCTS:	in order to avoid exothermic reactions. In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

**11 TOXICOLOGICAL INFORMATION**

ACUTE TOXICITY:	Gas or vapour is harmful on prolonged contact or in high concentration. This product can be hazardous when inhaled and/or touched. Irritant to eyes and mucous membranes.
LOCAL EFFECTS:	Hazardous in case of skin contact, irritant.
CHRONIC TOXICITY:	Repeated exposure may cause chronic eye irritation. May cause chemical eye burns. Swallowing concentrated chemical may cause severe internal injury, unconsciousness and death.

Contains no known category 1 or 2 carcinogens, mutagens or reproductive toxicants.

**PENETRANT****12 ECOLOGICAL INFORMATION**

<b>MOBILITY:</b>	Partially soluble in water. The majority of this product will evaporate within a day from water or soil surfaces leaving a chemical that
<b>PERSISTANCE AND DEGRADABILITY:</b>	will bind to particulate matter to form sediments. The majority of this product is inherently biodegradable, oxidising rapidly by photochemical reactions in air. The remaining chemicals degrade in soil to form smaller molecules, which are either biodegraded in soil or volatised into the air.
<b>BIO ACCUMULATION: ECOTOXICITY:</b>	This product has the potential to bio accumulate. This product is not classified as harmful to the environment.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

<b>UN NUMBER:</b>	UN1950
<b>SHIPPING NAME:</b>	Aerosols
<b>HAZARD CLASS:</b>	2.1 (for Sea Transport). Classification code 5F
<b>EmS:</b>	F-D, S-U
<b>CLASS:</b>	2
<b>LABELLING:</b>	2.1

**15 REGULATORY INFORMATION****LABELLING:**

Extremely flammable



Irritant

**RISK PHRASES**

R12	Extremely flammable
R36	Irritating to eyes
R38	Irritating to skin
R51/53	Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness

**SAFETY PHRASES**

S2	Keep out of the reach of children
S9	Keep container in a well ventilated place
S16	Keep away from sources of ignition – no smoking
S23	Do not breathe gas/fumes/vapour/spray
S24	Avoid contact with skin
S25	Avoid contact with eyes
S29	Do not empty into drains

S36	Wear suitable protective clothing
S46	If swallowed, seek medical advice immediately and show this container or label
S51	Use only in well-ventilated areas

No chemical safety assessments have been carried out for any of the substances used in this preparation.

## PENETRANT

### 16 OTHER INFORMATION

USES ADVISED AGAINST: The product should not be used for any other purpose other than its intended use. Handling, storage and conditions to avoid instructions must be followed at all times.

The information contained in this safety data sheet is provided in accordance with the requirements of the Chemical (Hazard Information and Packaging) Regulations. The information we have provided is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. The information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.