

SWP CRACK DETECTOR CLEANER NPD2416

Page: 1

Compilation date: 17/11/2015

Revision date: 13/12/2019

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: SWP CRACK DETECTOR CLEANER NPD2416

Product code: 1802

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	SPECIALISED WELDING PRODUCTS
	UNIT 1A
	FARRINGDON INDUSTRIAL CENTRE
	FARRINGDON
	NR ALTON, HAMPSHIRE
	GU34 3DD
	England
Tel:	+44 (0)1420 588180
Email:	sales@swp.uk.net

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the subst	ance or mixture
Classification under CLP:	STOT SE 3: H336; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Aerosol 1: H222;
	Skin Irrit. 2: H315; -: H229
Most important adverse effects:	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin
	irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to
	aquatic life with long lasting effects.
2.2. Label elements	
Label elements:	
Hazard statements:	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark



SWP CRACK DETECTOR CLEANER NPD2416



Signal words:	Danger
Precautionary statements:	P102: Keep out of reach of children.
	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
	P211: Do not spray on an open flame or other ignition source.
	P251: Do not pierce or burn, even after use.
	P362+P364: Take off contaminated clothing and wash it before reuse.
	P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122
	°F.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-151-9	64742-49-0	-	Aquatic Chronic 2: H411; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3:	30-50%
			H336	

PETROLEUM GASES, LIQUEFIED

	, _ , _ , _ , _ , _ , _ , _ ,			
270-704-2	68476-85-7	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	30-50%
PROPAN-2-OL				
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	10-30%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.		
	Drench the affected skin with running water for 10 minutes or longer if substance is still		
	on skin.		
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.		
Ingestion:	Do not induce vomiting. Consult a doctor.		

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

Page: 2



SWP CRACK DETECTOR CLEANER NPD2416

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour

mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of

ignition. If outside do not approach from downwind.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may produce sparks. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

Smoking is forbidden. Use non-sparking tools.



SWP CRACK DETECTOR CLEANER NPD2416

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct

sunlight. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1000mg/m3	-	-	-

PETROLEUM GASES, LIQUEFIED

UK	1,750mg/m3	2,180mg/m3	-	-
PROPAN-2-0	L			
UK	999 mg/m3	1250 mg/m3	-	-

DNEL/PNEC Values

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	773mg/kg/day	Workers	Systemic
DNEL	Inhalation	2035mg/m3	Workers	Systemic
DNEL	Dermal	699mg/kg/day	Consumers	Systemic
DNEL	Inhalation	608mg/m3	Consumers	Systemic
DNEL	Oral	699mg/kg/day	Consumers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Chemically resistant gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.



SWP CRACK DETECTOR CLEANER NPD2416

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Colourless

Odour: Characteristic odour

Flash point°C: <23

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

DERMAL	RAT	LD50	>2000	mg/kg
GASES	RAT	4H LC50	>20	mg/l
ORAL	RAT	LD50	>2000	mg/kg



SWP CRACK DETECTOR CLEANER NPD2416

Page: 6

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

 Skin contact:
 No data available.

 Eye contact:
 No data available.

 Ingestion:
 No data available.

 Inhalation:
 No data available.

 Delayed / immediate effects:
 Immediate effects can be expected after short-term exposure.

 Other information:
 Not applicable.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

ALGAE	72H IC50	<10	mg/l
DAPHNIA	48H EC50	<10	mg/l
FISH	96H LC50	<10	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.



SWP CRACK DETECTOR CLEANER NPD2416

Page: 7

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Recovery operations:
 Not applicable.

 Disposal of packaging:
 Not applicable.

 NB:
 The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

Marine pollutant: No

by the supplier.

Section 16: Other information

Other information

 Other information:
 This safety data sheet is prepared in accordance with Commission Regulation (EU) No

 2015/830.

 Phrases used in s.2 and s.3:
 H220: Extremely flammable gas.

 H222: Extremely flammable aerosol.

 H225: Highly flammable liquid and vapour.



SWP CRACK DETECTOR CLEANER NPD2416

Page: 8

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Please note that due to the on-going change in regulation from CHIP to CLP, any MSDS information supplied by LMA is only considered accurate at the time of its creation. During this time classifications of substances may change. Therefore it is possible that can art work and MSDS information may differ. As such if you have any concerns we recommend you request a new MSDS from us every 6-12 months.