

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** FLUXAL 1265
- **Article number:** 1265/1
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Product category** PC38 Welding and soldering products (with flux coatings or flux cores.), flux products
- **Application of the substance / the mixture** Brazing flux
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Specialised Welding Products Ltd
- Unit 1, Farringdon Industrial Centre, Farringdon, Nr Alton, Hampshire GU34 9DD, UK
- Tel: +44 (0)1420 588180, Email: sales@wsp.uk.net
- **1.4 Emergency telephone number:** +44 (0)1420 588180
- www.specialisedwelding.co.uk

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms** GHS07, GHS08

- **Signal word** Warning

- **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P362 Take off contaminated clothing and wash before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

Trade name: FLUXAL 1265

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 7447-41-8 EINECS: 231-212-3	lithium chloride ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	10-<25%
CAS: 13775-53-6 EINECS: 237-410-6 Reg.nr.: 01-2119511565-43-xxxx	sodium cryolite ☠ STOT RE 1, H372; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H332	2.5-<10%
CAS: 7681-49-4 EINECS: 231-667-8 Reg.nr.: 01-2119539420-47-xxxx	sodium fluoride ☠ Acute Tox. 3, H301; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-<10%

· **Additional information** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation** In case of unconsciousness place patient stably on their side for transportation.

· **After skin contact** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing** Do NOT induce vomiting, do NOT drink, seek medical advice

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Hydrogen fluoride (HF)

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear fully protective suit.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures** Not required.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

· **6.3 Methods and material for containment and cleaning up:**

Dispose of contaminated material as waste according to item 13.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** Prevent formation of dust.

(Contd. on page 3)

Trade name: FLUXAL 1265

(Contd. of page 2)

- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Advised preservation period under normal storage conditions: 6 months.
- **Storage class**
- **Class according to regulation on flammable liquids:** Void
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

· 8.1 Control parameters

- **Components with limit values that require monitoring at the workplace:**

7681-49-4 sodium fluoride

WEL	Long-term value: 2.5 mg/m ³ as F
-----	--

- **DNELs**

13775-53-6 sodium cryolite

Dermal	DNEL	1020 mg/kg bw/day (worker) (systemic long term effect)
Inhalative	DNEL	99.8 mg/m ³ (worker) (systemic & local acute effect) DNEL(worker) = 0.1mg/m ³ for systemic & local long term effect

- **PNECs**

13775-53-6 sodium cryolite

PNEC	0.0048 mg/l (Fresh water)
	0.0048 mg/l (Sea water)
	30.5 mg/kg (sediment (fresh water))
	214 mg/kg (sediment (sea water))

- **Additional information:** The lists that were valid during the creation were used as basis.

· 8.2 Exposure controls

· Personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to a lack of tests, no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Glove material

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Trade name: FLUXAL 1265

(Contd. of page 3)

- **Penetration time of glove material**
The exact penetration time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Powder

Colour: White

· Odour: Odourless

· Odour threshold: Not determined.

· pH-value: Not applicable.

· Change in condition

Melting point/Melting range: undetermined

Boiling point/Boiling range: undetermined

· Flash point: Not applicable

· Flammability (solid, gaseous) Not determined.

· Ignition temperature:

Decomposition temperature: Not determined.

· Self igniting: Product is not self igniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

· Vapour pressure: Not applicable.

· Density: Not determined

· Relative density Not determined.

· Vapour density Not applicable.

· Evaporation rate Not applicable.

· Solubility in / Miscibility with

Water: Soluble

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

dynamic: Not applicable.

kinematic: Not applicable.

Organic solvents: 0,0 %

Solids content: 100,0 %

· 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known

· 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 5)

Trade name: FLUXAL 1265

(Contd. of page 4)

- **10.5 Incompatible materials:** Avoid strong acids
- **10.6 Hazardous decomposition products:** Danger of toxic fluorine based pyrolysis products

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values that are relevant for classification:**

13775-53-6 sodium cryolite

Oral	LD50	>5000 mg/kg (rat)
	LDL0	9000 mg/kg (rabbit)
Dermal	LD50	>2100 mg/kg (rat)
Inhalative	LC50	>4470 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.

- **Type of test** **Effective concentration** **Method** **Assessment**

13775-53-6 sodium cryolite

CE50 / 48h	156 mg/l (daphnia) (daphnia magna)
CL50	8.8 mg/l (algae) (scenedesmus capricornutum)
	4.47 mg/l (rat) (4h)
CL50 / 96h	99 mg/l (fish) (brachydanio rerio)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 6)

Trade name: FLUXAL 1265

(Contd. of page 5)

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**
Must apply in all cases all local, regional and national laws and European directives. The end user must determine the specific code of waste for each industry using the appropriate European Code European Waste Catalogue. It is recommended that all details are specified by the responsible waste.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

SECTION 14: Transport information

- | | |
|---|-----------------|
| · 14.1 UN-Number | Void |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name | Void |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) | Void |
| · ADR, ADN, IMDG, IATA | Void |
| · Class | Void |
| · 14.4 Packing group | Void |
| · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | No |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- National regulations
- Classification according to VbF: Void
- Technical instructions (air):

Class	Share in %
III	<25

- Customs Combined Nomenclature : 38.10.90.90.00
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

 GB
 (Contd. on page 7)

Trade name: FLUXAL 1265

(Contd. of page 6)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· **Department issuing MSDS: Technical service**