



## INSPECTION CERTIFICATE According to EN 10204 3.1

CUSTOMER : SPECIALISED WELDING PRODUCTS-U.K.					MTR NO. / ISSUE DATE		EXP-411/10.11.2022							
					PART NO.		7216							
INVOICE NO./P.O. NO. : EXP/22-23/528 DT-10.11.2022/41482 DT-05.09.2022					BATCH NO.		T-13546							
					GRADE		ER 308L/(W 19 9 L)							
					SUPPLY CONDITION		STAINLESS STEEL TIG WELDING WIRE							
					SURFACE FINISH		BRIGHT DRAWN, BRIGHT FINISH							
<b>CHEMICAL COMPOSITION OF WIRE :-</b>														
SR. NO.	DIAMETER (mm)	NUMBER OF PKTS	WEIGHT (KGS)	HEAT NO SPECIFIED	%C	%Mn	%Si	%S	%P	%Cr	%Ni	%Cu	%Mo	%N2
<b>ELEMENTS %</b>				<b>MIN</b>	-	<b>1.00</b>	-	-	-	<b>19.00</b>	<b>9.00</b>	-	-	-
				<b>MAX</b>	<b>0.030</b>	<b>2.50</b>	<b>0.65</b>	<b>0.020</b>	<b>0.030</b>	<b>21.00</b>	<b>11.00</b>	<b>0.50</b>	<b>0.50</b>	-
1	1.60 X 1000	25	500.00	<b>38LIF140A</b>	0.021	1.70	0.37	0.007	0.027	19.61	9.04	0.14	0.110	0.0612
<b>MECHANICAL PROPERTIES OF ALL WELD METAL :-</b>														
SL. NO.	TENSILE STRENGTH	0.2% PROOF STRESS	ELONGATION %	REDUCTION OF AREA %	CHARPY IMPACT VALUE (Joules) Temp. AT (RT)	FERRITE NO (FN) (WRC-1992)	INCLUSION RATING							
							A	A	A	A	A			
-	(N/mm <sup>2</sup> )	(N/mm <sup>2</sup> )	Lo=100	-	-	-	THICK THIN	THICK THIN	THICK THIN	THICK THIN	THICK THIN	THICK THIN	THICK THIN	THICK THIN
1	638	478	36	72	104	11	-	-	-	-	-	-	-	-
<b>SPECIFICATION :-</b>														
TENSILE STRENGTH DIAMETER TOLERANCE % ELONGATION MATERIAL SPECIFICATION				AS PER DIN EN ISO 14343-A AS PER ISO 544 STANDARD MATERIAL CONFORMS TO DIN EN ISO 14343-A										
MATERIAL IS FREE FROM MERCURY CONTAMINATION , FREE FROM WELD AND WELD REPAIRS . <b>RADIOACTIVITY TEST</b> : WE CONFIRM THE MATERIAL HAS BEEN TESTED AND FOUND TO BE FREE FROM RADIOACTIVE CONTAMINATION.														
<b>WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED ABOVE HAS BEEN TESTED AND COMPLIES WITH THE TERMS OF ORDER / CONTRACT.</b>														