Air Line 15 Accessories







Contents

Air Line Accessories

Sanding/Polishing Pads & Belts	464
Air Adaptors / Quick Couplings	464
Composite Quick Couplings	464
Standard Air Couplings	465
Euro Air Couplings	465
Genuine PCL 60 Series Air Couplings	465
Genuine PCL 100 Series Air Couplings	465-466
Clear Braided PVC Hose	466
Rubber Whip Hoses	466
Rubber Hose Assemblies	466
UPVC Re-Coil Hoses	466
Air Hose Reels	466
Inlet Air Units, Filters & Regulators	467
Dual Scale Pressure Gauges	467
Air Adjusting Valve	467
Caulking Gun	468
Underseal Gun	468
Air Grease Gun	468
Standard Safety Tips	468
Tyre Inflator	468
Air Blow Guns	468
Lubrication Set	469
Lubrication Kit & Applicator	469
Air Line Oils	469
Magnetic Impact Wrench Holder	469

Sanding/Polishing Pads & Belts

SP01

6" Sanding Pad Vinyl Face



SP06

5" Sanding Pad Velcro Face



SB10L-60 60 Grit SB10L-80 80 Grit SB10L-120 120 Grit



SP02

6" Sanding Pad Velcro Face



SP07

5" Sanding Pad Vinyl Face – 6 holes



1

SP03

SP09 2" Sanding Pad Velcro Face

6" Sanding Pad

Velcro Face - 6 holes



SP05

5" Sanding Pad Vinyl Face



SP010

7" Buffing Pad



SB10-60 60 Grit SB10-80 80 Grit SB10-120 120 Grit



SB20-60 60 Grit SB20-80 80 Grit SB20-120 120 Grit



Air Adaptors / Quick Couplings

SY-211M

1/4" Male Adaptor



SY-211F

1/4" Female Adaptor



SY-210M

1/4" Male Adaptor



SY-210F

1/4" Female Adaptor



Composite Quick Couplings

Male - PT

SY-0213M ¹/4" **SY-0313M** ³/8"

SY-0413M 1/2"

SY-2213P 5x8 **SY-2313P** 6.5x10 **SY-2413P** 8x12









Female - PT

SY-1213F 1/4" PT **SY-1313F** 3/8" PT **SY-1413F** 1/2" PT

SY-3113H 10SH ¹/4" **SY-3213H** 20SH ⁵/16" **SY-3313H** 30SH ³/8" **SY-3413H** 40SH ¹/2"





Standard Air Couplings



Size
1/4"
3/8"
1/2"



Part No.	Size
BSF20-14	1/4"
BSF20-38	3/8"
BSF20-12	1/2"



Part No.	Size
BPH20-14	1/4"
BPH20-516	5/16"
BPH20-38	3/8"



Part No.	Size
BPM20-14	1/4"
BPM20-38	3/8"
BPM20-12	1/2"



Part No.	Size
BPF20-14	1/4"
BPF20-38	3/8"
BPF20-12	1/2"

Euro Air Couplings



Part No.	Size
ESM20-14	1/4"
ESM20-38	3/8"
ESM20-12	1/2"



Part No.	Size
ESF20-14	1/4"
ESF20-38	3/8"
ESF20-12	1/2"



Part No.	Size
EPM20-14	1/4"
EPM20-38	3/8"
EPM20-12	1/2"



Genuine PCL 60 Series Air Couplings



1, 20	10.0
Part No.	Size
BSM60-14	1/4"
BSM60-38	3/8"
BSM60-12	1/2"



1	
Part No.	Size
BSF60-14	1/4"
BSF60-38	3/8"
BSF60-12	1/2"







Genuine PCL 100 Series Air Couplings





-	-
Part No.	Size
BSM100-38	3/8"
BSM100-12	1/2"




-	_
Part No.	Size
BSF100-38	3/8"
BSF100-12	1/2"



Part No.	Size
BPH100-38	3/8"
BPH100-12	1/2"





100 Series

Adaptor

Female

Male to Male Connector

Part No.	Size
DC2-14	1/4"
1310	3/8"
DC2-12	1/2"

Ma



D	ou	ble	Hose	Tai	l
---	----	-----	------	-----	---

Part No.	Size
DHT-14	1/4"
DHT-516	5/16"
DHT-38	3/8"
DHT-12	1/2"



Twin Airflow Coupling

Part No.	Size
6103	- 80



ale to Female Reducer	Standard Tailniece 1/4" Ma
	Standard Tailniece 1/4" Ma

MFR-3814	3/8"	1/4"		AND IN
MFR-1214	1/2"	1/4"	(Bull))ii
MFR-1238	1/ _{2V}	3/8"		



3/8" Bore

1/2" Bore



Female to Female Reducer

Part No.	Size	Size	
FFR-3814	3/ _{8V}	1/4"	
FFR-1214	1/2"	1/4"	



Swivel Connector ¹	/4"
Part No.	Size
E107-8	1/4"

TP-38

TP-12



Mini Lubricator – Br	ass
Part No.	Size
EW-B42	1/4"





Part No. JF-1



Clear Braided **PVC Hoses** 30 metres



1374	PVC 3/ ₁₆ " Nylon Braided Hose – 8 Bar requires 3/ ₈ O-Clip
1327	PVC 1/4" Nylon Braided Hose – 8 Bar requires 3/8 0-Clip
1328	PVC $5/_{16}$ " Nylon Braided Hose – 7 Bar requires $1/_2$ O-Clip
1329	PVC 3/8" Nylon Braided Hose – 7 Bar requires 9/16 O-Clip





WH38-0514M	0.5m x 3/8" Hose c/w 1/4" BSPM Fittings
WH38-0538M	0.5m x 3/8" Hose c/w 3/8" BSPM Fittings
WH38-05A	0.5m x ³ / ₈ " Hose c/w ¹ / ₄ " BSPF Fittings
WH12-05A	0.5m x 1/2" Hose c/w 1/2" BSPF Fittings
WH12-05B	0.5m x 1/2" Hose c/w 1/2" BSPF and Quick Connect Fittings

Rubber Hose **Assemblies** BS5118/2

- 20 Bar working pressure
- 60 Bar burst pressure



AH8-5	5m x 5/ ₁₆ " Hose c/w 1/ ₄ " BSP Fittings
AH8-10	10m x 5/ ₁₆ " Hose c/w 1/ ₄ " BSP Fittings
AH8-15	15m x 5/ ₁₆ " Hose c/w 1/ ₄ " BSP Fittings
AH8-20	20m x 5/ ₁₆ " Hose c/w 1/ ₄ " BSP Fittings
AH96-5	5m x ³ / ₈ " Hose c/w ¹ / ₄ " BSP Fittings
AH96-10	10m x 3/8" Hose c/w 1/4" BSP Fittings
AH96-15	15m x ³ / ₈ " Hose c/w ¹ / ₄ " BSP Fittings
AH96-20	20m x ³ / ₈ " Hose c/w ¹ / ₄ " BSP Fittings
AH8-100	100m x 5/ ₁₆ " Hose
AH96-100	100m x 3/8" Hose
AH13-100	100m x ¹ / ₂ " Hose

UPVC Re-Coil Hoses



RH14-25	1/4" UPVC Re-Coil Hose
RH38-25	3/8" UPVC Re-Coil Hose

Air Hose Reels 15 metres

- Can be mounted on wall or ceiling
- PU tube anti-explosion capability up to 300 PSI
- Convenient auto retractable hose



Part No.	Male Fitting	Hose Size	Working Pressure	Burst Pressure	Weight kg	
SA-3215	1/4"	5/ ₁₆ " (8mm)	90 (6.3)	300 (20.7)	5.0	
SA-3315	1/4"	3/8" (10mm)	90 (6.3)	300 (20.7)	6.0	



AFRL80-14

1/4" Inlet Air Unit

Filter/Regulator/Lubricator

- Regulate pressure: 10-120 PSI
- Max pressure: ≤140 PSI

AFRL80-12

1/2" Inlet Air Unit

Filter/Regulator/Lubricator

- Regulate pressure: 10-120 PSI
- Max pressure: ≤140 PSI



BC2000

1/4" Inlet Air Unit

Filter/Regulator/Lubricator

- Regulate pressure: 10-120 PSI
- Max pressure: ≤140 PSI

BC4000

1/2" Inlet Air Unit

Filter/Regulator/Lubricator

- Regulate pressure: 10-120 PSI
- Max pressure: ≤140 PSI



AF80-14

1/4" Inlet Air Unit

Filter only

■ Max pressure: ≤140 PSI

AF80-12

1/2" Inlet Air Unit

Filter only

■ Max pressure: ≤140 PSI



AL80-14

1/4" Inlet Air Unit

Lubricator only

Max pressure: ≤140 PSI

AL80-12

1/2" Inlet Air Unit

Lubricator only

■ Max pressure: ≤140 PSI



AFR80-14

1/4" Inlet Air Unit

Filter/Regulator only

- Regulate pressure: 10-120 PSI
- Max pressure: ≤140 PSI

AFR80-12

1/2" Inlet Air Unit

Filter/Regulator only

- Regulate pressure: 10-120 PSI
- Max pressure: ≤140 PSI



AFRC-12

1/2" Pre/ Coalescing Air Unit

Filter/Regulator

- Dual pre/coalescing filter cartridge
- 25/0.01 micron filtration
- Max pressure 10 Bar (145 PSI)



AFC-12

1/2" Pre/ Coalescing Air Unit

Filter only

- Suitable for use when regulator is not required
- Dual pre/coalescing filter cartridge only
- 25/0.01 micron filtration



AFR6102A

Air Filter Regulator

1/4"

- Clear polycarbonate bowl
- Manual down valve
- Supplied with gauge and wall bracket

Dual scale pressure gauges



- Brass internal components
- Steel case construction
- Plastic front cover

REAR ENTRY CONNECTION

PG001	0-160 PSI, 40mm diameter, $^{1}/_{8}$ "
PG002	0-160 PSI, 50mm diameter, $1/8$ "
PG003	0-200 PSI, 50mm diameter, 1/4"
PG004	0-300 PSI 50mm diameter 1/4"

BOTTOM ENTRY CONNECTION


PG005	0-200 PSI, 50mm diameter, 1/	4'
PG006	0-300 PSI, 50mm diameter, 1/	/4'



AG3000-03

Air Filter Regulator





- Heavy duty aluminium cast body
- Pressure reducing valve with filter and pressure gauge diameter 40mm and two in-line cocks 1/4"



AG4000-04

Air Filter Regulator

1/2"

- Maximum pressure 12 Bar
- Heavy duty aluminium cast body
- Pressure reducing valve with filter and pressure gauge diameter 50mm and two in-line cocks 1/4"



PG-03

Air Adjusting Valve

V-103

Caulking Gun



BG-1

1/4" BSP Palm Blow Gun









JC-291 / JC-292 Standard Safety Tips To fit JC-313, JC-320, JC-340 (optional)

TG-90 1/4" BSP Tyre Inflator



JC-405, JC-412, JC-424

Air Blow Guns

Air inlet: 1/4"

JC-640

Super Air Blow Gun Air inlet: 1/4"

Part No.	Length inch	Nozzie Pressure PSI (Bar)	Working Pressure PSI (Bar)	Maximum Consumption 1/4 Hose CFM (I/min)	Average Air Consumption 3/8 Hose CFM (I/min)	Air Hose inch	Sound Pressure dBA	Net Weight Ibs (kg)
JC-405	5	75-120 (5.3-8.5)	150 (10.6)	13.0 (368)	15.0 (425)	3/8	90.0	0.24 (0.11)
JC-412	12	75-120 (5.3-8.5)	150 (10.6)	13.0 (368)	15.0 (425)	3/8	90.0	0.28 (0.13)
JC-424	24	75-120 (5.3-8.5)	150 (10.6)	13.0 (368)	15.0 (425)	3/8	90.0	0.31 (0.14)
JC-640	40	75-120 (5.3-8.5)	150 (10.6)	13.0 (368)	15.0 (425)	3/8	90.0	0.75 (0.34)

468



SO-10T

Lubrication Set – 8 pieces

- Multi Purpose Grease
- Working Temperature: -20 to 180°C



Air Line / Compressor Oil

AIR500	5 litre Air Line Oil
AIR100	1 litre Air Line Oil
COMP500	5 litre Compressor Oil
COMP100	1 litre Compressor Oil



SG-101

Lubrication Kit

- + Applicator
- Multi Purpose Grease
- Working Temperature: -20 to 180°C



SH-1001

Magnetic 1/2" Impact Wrench

Holder



- For Pneumatic Tools
- Density @ 15°C: 0.899Viscosity @ 40°C: 23.1cSt
- Appearance: Clear green liquid

AIR050	Air Tool Oil – 500ml
AIR025	Air Tool Oil – 250ml

