



PRODUCT DATA SHEET

Part No. **1825 1826 1827 1829**

Description:

New Fire High temperature resistant fiber cloth soft, flame retardant, high temperature resistant, 100% do not contain asbestos composition, with low bulk density, insulation, antioxidant and other properties

Application:

Can make the aluminum foil, silicone, PU, such as dyeing, neoprene coating; Welding blanket; Fire blanket; Welding heat insulation blanket

特性 Characteristic	单位 Unit	数据 Data	测试标准 Method
织纹 Weave		破斜纹 3×1 TWILL	
用纱 Yarn	tex	经纱 WARP	纬纱 WEFT
		EC9 136 1×0	EC9 136 1×0
重量 Weight	g/m ²	430	ASTM-D3776-2009
厚度 Thickness	mm	0.4	ASTM-D1777-1996
密度 Thread Count	per cm	经纱 WARP 18 纬纱 WEFT 13	ASTM-D3775-2008
涂层类型 Coating			
涂层重量 Coating Weight	g/m ²		ASTM-D3776-2009
产品总重 Total Weight	g/m ²		ASTM-D3776-2009
产品总厚 Total Thickness	mm		ASTM-D1777-1996
抗张强度 Tensile Strength	N/2.5cm	经纱 WARP 2000 纬纱 WEFT 1500	ASTM-D5034-2001
耐温度 Service Temperature	°C	550	
获得认证 Certification		欧洲 BSEN 476 PART 7	
		欧洲 BSEN 1869	
		欧盟 CE	
		美国 FM 4950	

标准幅宽 Width m 1/1.30/1.55/1.22
标准卷长 Length m 50

备注 Remarks

Specialised Welding Products Ltd

Unit 1, Withins Point, Withins Road, Haydock Industrial Centre, Haydock, WA11 9UD, UK T: 01942 719930 E: sales@swp.uk.net

www.specialisedwelding.co.uk