

#### Wir machen Edelstahl erst wertvoll

# **Derustit 4067 - Neutralising Paste**

## PRODUCT DESCRIPTION AND POSSIBLE APPLICATIONS

**Description:** pasty mixture lime milk

**Intended use:** neutralization of pickling paste residues on stainless steel surfaces

**Suitable for:** • stainless steel parts treated with pickling paste

**Handling methods:** pickling brush (acid-resistant)

**Advantages:** • save rinsing of parts

**Packing sizes:** plastic tub (2 kg - 4 tubs in one cardboard box)

### **INSTRUCTIONS FOR USE**

**General notes:** Please respect safety data sheet and instructions for use. Reaction times and

results depend on different factors. Practical tests with sample parts should be

carried out to define the optimum parameters.

**Preparation:** Shake well before application or stir thoroughly with a plastic stick!

**Application:** Apply product evenly and mix with the pickling paste

**Reaction time:** Neutralisation sets in immediately

**Further treatment:** Thoroughly rinse treated parts with water until rinsing water is neutral. **Please note:** Use water with a hardness of < 10° dH in order to minimize water stains

and lime residues!

**Additional notes:** Do not use at high temperatures or under direct sunlight.

Neutralisation of pickling paste can and must not replace waste water

treatment.

## **REMARKS ON DANGERS AND SAFETY PRECAUTIONS**

**General notes:** The user is responsible for the compliance with legal regulations.

In case of improper use, Derustit disclaims liability for possible damages.

Classification: Not hazardous as per ADR/RIDC

XI (irritant)

**Remarks on storage:** Store product in tightly closed original container and inaccessible for

unauthorized persons. Make sure that storing area is furnished with good

aeration and a floor coating which is adapted to the components.

Store in accordance with national and regional regulations! Protect from heat

and sunlight. Storing temperature: 5 to 25 °C.

**Shelf life:** 12 months.

**Protective equipment:** Wear suitable protective equipment as per safety data sheet.

**Exhaust air:** Make sure that working area is well ventilated.

Waste water/disposal: Untreated product and rinsing water must not be lead into sewerage system.

Tel.: +49 (0)6074 4903 0 Fax: +49 (0)6074 4903 33 Email: <u>info@derustit.de</u> www.derustit.de