

PRODUCT DATA SHEET

PERSPECTA 9000 spectacle

Part Numbers:

10045516
10045517
10045518
10045519
10045640



COMPONENTS	MATERIALS	FEATURES
Lens	Polycarbonate	Wrap around design with side protection
Frame	Polycarbonate	Integral to lens
Side Shields	Polycarbonate	Integral to lens/temple
Nose Piece	Bridge – Polycarbonate	Integral to lens
	Nose Pad – PVC	Snap in
Temple	Polycarbonate/TPE	Co-injected with soft cushion tip
Hinge	Nylon	Integral to lens/temple
Screw	Stainless Steel	Standard hinge screw

WEIGHT: 26 g

SPECIAL FEATURES

- Incredibly light, resilient and durable protective eyewear for all day wear
- Snug-fitting wrap around lens, low energy impact resistance
- Special nose pads secure the spectacles to your face without slipping and provide a pillow soft fit
- Lens with base curvature 9.75 for wide and unobstructed vision
- Fashionable design resembles sunglasses, suitable for both men and women
- Revolutionary co-injected temples bring you the most comfortable feeling
- Filters out 99.9% of harmful UV radiation
- Sightgard coating: MSAs popular anti-fog coating with good anti-scratch properties
- TuffStuff coating: Antiscratch according to EN 166 "K"

FRAME AND LENS OPTIONS

- 10045516** translucent light blue/blue frame, clear lens: TuffStuff coating, filter 2C-1.2 (12 pcs)
10045517 translucent light blue/blue frame, clear lens: Sightgard coating, filter 2C-1.2 (12 pcs)
10045518 smoke/blue frame, smoke lens: Sightgard coating, filter 5-2.5 (12 pcs)
10045519 translucent amber/blue frame, amber lens: Sightgard coating, filter 2-1.2 (12 pcs)
10045640 smoke/blue frame, blue mirror lens: Sightgard coating, filter 5-2.5 (12 pcs)

MARKINGS / APPROVALS

- | | |
|--|------------------------------------|
| - Standard Number | EN166 |
| - Mechanical resistance to impact | F (low energy impact 45m/s) |
| - Certification mark | CE |
| - Optical class (best class, for permanent wear) | 1 |
| - Additional resistance at extreme temperatures (-5 and 55 °C) | T |
| - Resistance to surface damage by fine particles (TuffStuff coating) | K |

2C-1.2 UV radiation with good color recognition. Does not protect against sun glare.

5-2.5 Offers adequate protection against sun glare.

PACKAGING

12 pcs / dispenser box
144 pcs / master carton

MSA Europe
Phone +49 (30) 68 86-0
E-Mail info.de@MSAsafety.com
www.MSAsafety.com

Subject to changes without prior notice. Rev03, 01.2013

