Selected by Professionals

IG MACHINES CT INFORMATION





















Ste)Ith

SWP

Ste)Ith

9014H-AC - Air Cooled 9014H-WC - Water Cooled

G 500F LCD

Dual Pulse

PRODUCT SUMMARY

A 500 amp separate wire feed dual pulse Mig welder with the option of Air Cooled or Water Cooled. Both models are supplied with their necessary torch and regulator. The machine also offers Tig/MMA and has an easy-to-navigate LCD screen.

FEATURES

- Heavy industrial use
- Waveform control for added stability of the arc even at low currents
- Variable amperage control with digital meter for simultaneous welding current and tension display
- Equipped with temperature, voltage and current sensors for high protection
- Optional trolley and water cooling unit
- M501-4 torch and 2068 regulator included
- M36-3 and 2068 regulator included with air cooled package

Input power voltage (V)	3~400		
	MIG	TIG	MMA
Rated input power (KW)	23	18	23
Rated input power (A)	41.4	34.4	41.8
Effect current (A)	32.1	26.6	32.6
Duty cycle (A) (40°C 10 min)	60% @ 500		
		100%@400	
No load voltage (V)	87	92.6	95.8
Welding current range (A)	10-500		
Welding voltage range (V)	10-50		
Protection class		IP23	
Efficiency (%)		85	
Insulation class		Н	
Cooling		Air	
Overall dimensions (mm)	605 x 240 x 445		
Weight (kg)	31.5		
Accessories included	3m Argon hose, 3m earth return lea		





