



Selected by Professionals

Stealth

WELDING MACHINES PRODUCT INFORMATION

300mm (20kg)	LCD 320 x 480 TFT	3 PHASE 50/60Hz	PROTEC ADV	VRD safe	MCU Control System	SPOOL GUN	3 PROOF	Generator Friendly
550V Tested in Production	Voltage Reduction Device	MCU Control System	Spool Gun	Moisture ✓ Salt Spray ✓ Corrosion ✓	Generator Friendly			

9015H DIGI-MULTI MIG 200 PRO 4-in-1 Multi-Process

PRODUCT SUMMARY

An impressive multi-process machine capable of MIG SYNERGIC/AC/DC PULSE TIG/MMA. Compact and weighs only 21kg, has direct selection of SYN parameters and intuitive setting of parameters can increase efficiency and productivity. Also features an easy to navigate LCD screen.

OPTIONAL EXTRAS

- D3595-1-1** Adaptor 3/8 Power x 3/8 BSP Hose Fitting
- WP17F-12SZ** Torch Package c/w Switch and Sheath
- WP18AK** Accessory Kit
- EH52LD** 200A Electrode Holder c/w 35-50 dinze 3m



SPECIFICATIONS

Input power voltage (V)	110/230±10%		
Frequency (Hz)	50/60		
	MIG	TIG	MMA
Effective current – 110V	20.5	19.8/19.3 (AC/DC)	19.2/20.2 (AC/DC)
Effective current – 230V	15.4	12.2/12.1 (AC/DC)	15.2/16.7 (AC/DC)
Duty cycle (A) (40°C 10 min) – 110V	30% @ 200	30% @ 200	30% @ 200
Duty cycle (A) (40°C 10 min) – 110V	60% @ 145	60% @ 145	60% @ 145
Duty cycle (A) (40°C 10 min) – 110V	100% @ 110	100% @ 110	100% @ 110
Duty cycle (A) (40°C 10 min) – 220V	30% @ 140	30% @ 160	25% @ 130
Duty cycle (A) (40°C 10 min) – 220V	60% @ 100	60% @ 115	60% @ 85
Duty cycle (A) (40°C 10 min) – 220V	100% @ 80	100% @ 90	100% @ 65
No load voltage – limited (V)	72V		
Welding current range (A) – 110V	30~140	10~160	10~130
Welding current range (A) – 230V	30~200	10~200	10~200
Welding voltage range (V) – 110V	15.5~21	10.4~16.4	20.4~25.2
Welding voltage range (V) – 230V	15.5~24	10.4~18	20.4~28
Efficiency (%)	80		
Power factor	0.99		
Insulation class	H		
Protection class	IP21S		
Cooling	Air		
Overall dimensions (mm)	610 x 220 x 410		
Weight (kg)	21		
Accessories included	3m Argon hose, 3m earth return lead		



Supplied with **2068 ARGON/CO₂ PRESSURE REGULATOR**
Single Stage 2g – Argon/
CO₂ Regulator – 30 lpm



and **M25-3 MIG TORCH** 3m Bladeswitch c/w Euro Fitting

