



Selected by Professionals

Stealth WELDING MACHINES PRODUCT INFORMATION



Input Voltage



Moisture ✓
Salt Spray ✓
Corrosion ✓



MCU Control System



Generator Friendly

9021H DIGI-ARC 175 LT 230V

PRODUCT SUMMARY

This MMA stick welder offers the ability to scratch start Tig. Easy read digital display, built in hot start with anti sticking and arc force. Lightweight with ability to weld 1.6 - 4.0 rods.

OPTIONAL EXTRAS

9806 Scratch Start Tig Package

9029 Carry Case



Supplied with
EARTH RETURN LEAD and **ELECTRODE LEAD**

Try our Super6 6013 electrodes or



	5.0kg	Diameter	Length
7401	2.5mm	350mm	
7402	3.2mm	350mm	

Vac-pac Superon 6013 electrodes.



	5.0kg	Diameter	Length
7601	2.5mm	350mm	
7602	3.2mm	350mm	

SCAN HERE FOR SWP WEBSITE



Perfect for the Stealth 9021H.

SPECIFICATIONS

Input power voltage (V)	230±10%	
Frequency (Hz)	50/60	
	MMA	TIG
Effective input current (A)	17	24
Maximum (KVA)	8.5	
Current adjustment range (A)	10-160	
Maximum no-load voltage (V)	62	
Duty cycle (A) (40°C 10 min)	40% @ 160	
	60% @ 135	
	100% @ 105	
Efficiency (%)	≤80	
Protection class	Ip23	
Insulation class	H	
Cooling	Air	
Electrode diameter (mm)	1.6-4.0	
Electrode type	6013, 7018, etc	
Overall dimensions (mm)	290 x 135 x 220	
Weight (kg)	4.5	
Accessories included	3m earth return lead + 3m electrode lead	

