

e≫lth **NG MACHINES** JCT INFORMATION

DIGI-ARC 205

▲ 🛛 (E 🗖



9023H DIGI-ARC 205 LT 定田

PRODUCT SUMMARY

A powerful MMA stick welder with excellent duty cycle and the ability to scratch start Tig. Easy read digital display, built in hot start with anti sticking and arc force. Lightweight, with the ability to weld 1.6mm - 4.0mm rods. Also supplied with a carry case



OPTIONAL EXTRAS

9807 Scratch Start Tig Package

	3	V	
		SWP ^R	
2	A CONTRACTOR OF	ALTH MILES	

STEXITY

Supplied with EARTH RETURN LEAD and ELECTRODE LEAD

Try our Super6 6013 electrodes or

				-
SPECIFICATIONS			Supe	26
Input power voltage (V)	230±	10%		
Frequency (Hz)	50/	60		
	TIG	MMA		
Effective input current (A)	25	37		
Maximum (KVA)	10.	8	Vac-	nac
Current adjustment range (A)	10-2	.00	- Vao	pae
Maximum no-load voltage (V)	61		C.	
Duty cycle (A) (40°C 10 min)	60% @	200	AS ING BRO	PER
	100% 0	© 155		Correlated Co
Efficiency (%)	≤8	5		
Protection class	lp2	3		6
Insulation class	Н			
Cooling	Ai	r	E Olar	Diama
Electrode diameter (mm)	1.6-	5.0	5.0kg	Diame
Electrode type	6013, 70	7601	2.5mn	
Overall dimensions (mm)	392 x 14	8 x 280	7602	3.2mn
Weight (kg)	6.1	2	7603	4.0mn
Accessories included	3m earth return lead,	3m electrode lead		
			Perf	ect

	and and a set of the s	and the second sec			
Suma		5.0kg	Diameter	Length	
Supero	Welding Electrodes	7401	2.5mm	350mm	Ī
	e nouroues	7402	3.2mm	350mm	
		7403	4.0mm	400mm	
Vac-pa	c Superon 6013 elect	rodes.			

	SUPER A ISO BERT 2000 CARE			
i.Okg	Diameter	Length	a company	
7601	2.5mm	350mm		J
7602	3.2mm	350mm		
7603	4.0mm	350mm		



in

0

f Tel: 01420 588180 | Email: sales@swp.uk.net | www.specialisedwelding.co.uk